



**ATC PT-B2720-W Wall Mount**  
**ATC PT-B2720-C Ceiling Mount**

- 1/3" Sensor
- 20x Optical Zoom f=4.7~94mm
- Pelco D/P
- High speed 400° rotation
- Heater & Blower / Service Video Output
- IP66 Outdoor
- DC12V / AC24V

**X20 OPTICAL ZOOM**

**1080P**  
**ALL-IN-ONE**  
**PTZ SPEED**  
**DOME CAMERA**

**HD-TVI / A-HD / HD-CVI**  
**Output Support**

**ATC PT-B2720**

<b>CAMERA</b>	
Image Sensor	1/3" Panasonic CMOS Sensor
Video Out	1080p ( A-HD / HD-TVI / HD-CVI )
Zoom	20 × Optical Zoom
Focal Length	20 ×: F1.6~3.5 , f=4.7~94mm
Minimum Illumination	Color: 0.5Lux, BW: 0.1Lux; Color DSS: 0.002Lux, BW DSS: 0.001Lux
Day & Night	Active/Passive/Day/Night/Schedule
Focus	Auto
Iris	0~20
Shutter Speed	1/30(25)~1/60000sec.
AGC	Off/On
White Balance	Auto
Mirror	None/Horizontal/Vertical/Horizontal & Vertical
WDR	High/Low/Disable
<b>PTZ</b>	
Pan/Tilt Range	Pan: 360° Endless, Tilt: 180°
Speed	Max. 400 degrees/sec.
Preset	254
Tour	8
Auto Scan	8
Pattern	4
Group	8
Schedule	16
Other PTZ Functions	Auto Flip, Parking Action, Power up Action
Protocol	Pelco D/P
<b>I/O</b>	
Alarm In	8CH
Alarm Out	4CH
<b>General</b>	
Dome Dimension	ø230mm x 325Hmm
Working Temperature	-42° C~+55° C
Working Humidity	90%
Fan	Start temp: 45° and 0°
Heater	0°
Power Supply	AC24V / DC12V (+/-10%)
Extra Video Out	Analog Output
Power Consumption	DC12V (26W), AC24V (65W)
Waterproof	IP66
Certificate	CE, FCC