

**4 PAIR 24 AWG
CATEGORY 5e Riser
TYPE CMR (Tested to 350 MHz)**



Compliance:

- UL 444, Communications Cable
- NEC Article 800
- ETL Verified to TIA-568-B.2, Category 5e
- UL Listed Type CMR
- C(UL) Listed Type CMG
- UL 1666 Riser Flame Test
- CSA C22.2 No. 214
- ICEA-S-80-576
- California State Fire Marshal Approved
- Restriction of Hazardous Substances (RoHS)

Applications:

- Gigabit Ethernet (1000Base-T)
- 100Base-T
- High Speed Voice/Data Applications
- 100Base-TX
- Video to the Desktop
- ISDN
- Multimedia
- 55/155 Mbps ATM
- 100Base VG-AnyLan

1.0 SCOPE:

- 1.1** This cable consists of 4 pair 24 AWG solid bare copper; color-coded HD Polyethylene insulation; overall white FR-PVC jacket.

2.0 CONSTRUCTION:

2.1 CONDUCTOR:

- 2.1.1 Material: Bare Copper
- 2.1.2 Size: 24 AWG
- 2.1.3 Construction: Solid

2.2 INSULATION:

- 2.2.1 Material: HD Polyethylene
- 2.2.2 Wall Thickness: .0076" nom.
- 2.2.3 O.D.: .036" nom.
- 2.2.4 Color code:
 - Pair 1: 1-Blue, 2-White-Blue
 - Pair 2: 1-Orange, 2-White-Orange
 - Pair 3: 1-Green, 2-White-Green
 - Pair 4: 1-Brown, 2-White-Brown

2.3 PAIRS:

- 2.3.1 2 conductors twisted together with a varying LHL.

2.4 CORE ASSEMBLY:

- 2.4.1 4 twisted pairs are cabled to form round core.

2.5 JACKET:

- 2.5.1 Material: FR-PVC
- 2.5.2 Wall Thickness: .014" nom.
- 2.5.3 OD: .180" nom.
- 2.5.4 Color: X (See chart below)
- 2.5.5 Ripcord run parallel under jacket
- 2.5.6 Markings PAIGE 9X2445EXYZ 24/4 PR SOL CAT5E 350 MHz CMR (****) 75° C XXXXXX (***) ROHS COMPLIANT (**) (*)

2.6 PUT-UPS:

- 2.6.1 Y Package Z length (See chart below)
- 2.6.2 Weight: 22 lbs / 1000'

X Jacket Color		Y Packaging	Z Length
1 – Gray	8 – Purple	B – Box	1 – 1000'
2 – White	9 – Orange	R – Reel/Spool	2 – 250'
3 – Red	B – Beige	S – Speed Coil	3 – 2500'
4 – Black	K – Pink		5 – 500'
5 – Blue	N – Green		
6 – Yellow	U – Unjacketed		
7 – Brown			

The information and specifications described herein are subject to error or omission and to change without notice.

Paige provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Paige be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Paige has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.



Paige[®] spec 9X2445EXYZ

(same as 710548Exx)

2.7 ELECTRICAL PROPERTIES

- 2.7.1 Temperature: 75°C
- 2.7.2 Voltage: 300 Volt
- 2.7.3 Mutual Capacitance: 14 pF/ft nom.
- 2.7.4 Char. Impedance: 100 Ohms ± 15
- 2.7.5 Propagation Delay Skew: 45 ns/100m max.
- 2.7.6 Velocity of Propagation: 70% nom.
- 2.7.7 DC Resistance: 9.38 Ohms/100m

Frequency MHz	Return Loss dB Minimum	Attenuation dB/100m Maximum	NEXT dB/100m Minimum	PSNEXT dB/100m Minimum
1	20.0	2.0	65.3	62.3
4	23.0	4.1	56.3	53.3
8	24.5	5.8	51.8	48.8
10	25.0	6.5	50.3	47.3
16	25.0	8.2	47.3	44.3
20	25.0	9.3	45.8	42.8
25	24.3	10.4	44.3	41.3
31.25	23.6	11.7	42.9	39.9
62.5	21.5	17.0	38.4	35.4
100	20.1	22.0	35.3	32.3

Frequency MHz	ELFEXT dB/100m Minimum	PSELFEXT dB/100m Minimum
1	63.8	60.8
4	51.7	48.7
8	45.7	42.7
10	43.8	40.8
16	39.7	36.7
20	37.7	34.7
25	35.8	32.8
31.25	33.9	30.9
62.5	27.8	24.8
100	23.8	20.8

Printing to be permanently identified via inkjet or print wheel print. (Embossed NOT Acceptable).

(*) Ascending / Descending Footage to Repeat Every 2 Feet.

(**) Manufacturer's lot number (for traceability)

(***) Cable Mill Factory Identification

(****) UL or ETL Listed & CSA Certified or C(UL)US Listed Acceptable

The information and specifications described herein are subject to error or omission and to change without notice.

Paige provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Paige be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Paige has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.