

# EYEMAX | 4K(8MP) CVI Outdoor IR Turret Camera, Starlight, True-WDR, Fixed Lens, UL-Listed, IR Range up to 197ft, IP67, Mic Built-in, DC12V



Starlight, 120dB True WDR, 3DNR • Max. 4K resolution • HD/SD switchable • Audio in interface, built-in mic • 2.8mm fixed lens • Max. IR length 50m, Smart IR • IP67, DC12V±30%

## System Overview

Experience 4K video surveillance with the simplicity of reusing existing coaxial infrastructure. The 4K HDCVI camera adopts a powerful ISP and advanced 1/2" image sensor, which provides superior high quality images. It also supports Starlight and 120dB true WDR for a clear image in poor lighting conditions. In addition, the camera features broadcast quality audio to provide enhanced supplementary evidence collection. Ultra-high definition and a complete set of features makes the 4K HDCVI camera an ideal choice for mid to large-size businesses and projects where both highly reliable surveillance and construction flexibility are demanded.

## FEATURES

- **4 Signals over 1 Coaxial Cable** : HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility. (\* Audio input is available for some models of HDCVI cameras)
- **Long Distance Transmission** : HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700m transmission for 4K and 4MP HD video via coaxial cable, and up to 300m via UTP cable.\* (\*Actual results verified by real-scene testing in Dahua's test laboratory)
- **Simplicity** : HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.
- **Starlight** : With the adoption of large sized high performance sensor, the camera is able to provide incomparable performance even under extreme lowlight environment. The starlight feature allows more details to be captured and accurate color to be recognized at night or in scenes with limited illumination.
- **Broadcast-quality Audio** : Audio information is used as supplementary evidence in video surveillance applications. The HDCVI camera supports audio signal transmission over coaxial cable. In addition, it adopts unique audio processing and transmission technology that best restores source audio and eliminates noise, guaranteeing the quality and effectiveness of collected audio information.
- **Multiple-formats** : The camera supports multiple video formats including HDCVI, CVBS, and other two common HD analog formats in the market. A DIP switch located on the cable allows you to quickly toggle formats, further simplifying installation and debugging. This feature makes the camera compatible with not only XVRs, but also most existing HD/SD DVRs.
- **Wide Dynamic Range** : Embedded with industry leading wide dynamic range (WDR) technology, vivid pictures are achieved even in the most intense contrast lighting conditions. True WDR (120dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.
- **Advanced 3DNR** : 3DNR is noise reduction technology that detects and eliminates random noises by comparing two sequential frames. Dahua's advanced 3DNR technology allows remarkable noise reduction with little impact to sharpness, especially under limited lighting condition. Besides, the advanced 3DNR effectively decreases the band width and saves the storage space.
- **Protection** : The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. Supporting  $\pm 30\%$  input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

# EYEMAX | 4K(8MP) CVI Outdoor IR Turret Camera, Starlight, True-WDR, Fixed Lens, UL-Listed, IR Range up to 197ft, IP67, Mic Built-in, DC12V

## SPECIFICATIONS

<b>Camera</b>	
Image Sensor	1/2" CMOS
Effective Pixels	3840(H)×2160(V), 8MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/4s~1/100,000s NTSC: 1/3s~1/100,000s
Minimum Illumination	0.005Lux/F1.5, 30IRE, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 50m (197ft)
IR On/Off Control	Auto / Manual
IR LEDs	2
<b>Lens</b>	
Lens Type	Fixed lens / Fixed iris
Mount Type	Board-in
Focal Length	2.8mm
Max Aperture	F1.6
Angle of View	H: 87° (110.8°/55°)
Focus Control	Auto / Manual
Close Focus Distance	2500mm (1800mm, 6100mm) 98.43" (70.87", 240.2')
<b>Dori Distance</b>	
Note: The DORI distance is a "general proximity" of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.	
Detect	Definition - 25px/m (8px/ft) Distance - 2.8mm:84m(276ft) / 3.6mm: 104m(341ft) / 6mm:164m(538ft)
Observe	Definition - 63px/m (19px/ft) Distance - 2.8mm:34m(112ft) / 3.6mm:42m(138ft) / 6mm:66m(217ft)
Recognize	Definition - 125px/m (38px/ft) Distance - 2.8mm:17m(56ft) / 3.6mm: 21m(69ft) / 6mm: 33m(108ft)

# EYEMAX | 4K(8MP) CVI Outdoor IR Turret Camera, Starlight, True-WDR, Fixed Lens, UL-Listed, IR Range up to 197ft, IP67, Mic Built-in, DC12V

Identify	Definition - 250px/m (76px/ft) Distance - 2.8mm:8m(26ft) / 3.6mm:10m(33ft) / 6mm:16m(52ft)
<b>Pan/Tilt/Rotation</b>	
Pan/Tilt/Rotation	Pan: 0° ~ 360° Tilt: 0° ~ 78° Rotation: 0° ~ 360°
<b>Video</b>	
Resolution	8MP (3840×2160)
Frame Rate	15fps@4K, 20fps@6MP, 25/30fps@4MP
Video Output	1-channel BNC high definition video output / CVBS video output (DIP switch)
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / WDR
WDR	120dB
Gain Control	AGC
Noise Reduction	2D/3D
White Balance	Auto / Manual
Smart IR	Auto / Manual
<b>Certifications</b>	
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
<b>Interface</b>	
Audio Inderface	1ch in & Built-in Mic
<b>Electrical</b>	
Power Supply	AC 24V±30% / DC 12V±30%
Power Consumption	Max 8W (12VDC, IR on)
<b>Environmental</b>	
Operating Conditions	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH * Start up should be done at above-30°C (-22°F)
Storage Conditions	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection & Vandal Resistance	IP67

# EYEMAX | 4K(8MP) CVI Outdoor IR Turret Camera, Starlight, True-WDR, Fixed Lens, UL-Listed, IR Range up to 197ft, IP67, Mic Built-in, DC12V

<b>Construction</b>	
Casing	Aluminium
Dimensions	Φ122mm×107mm (Φ4.8"×4.2")
Net Weight	0.5kg (1.10lb)
Gross Weight	0.62kg (1.37lb)