

CMIP3122-28

2MP IP Dome Camera

KEY FEATURES

- 2 MP 1/3" CMOS Sensor
- 2.8mm Fixed Lens
- Low profile / Compact size
- 3-Axis (Pan: $\pm 15^\circ$, tilt: $0 \sim 90^\circ$, rotation: $\pm 15^\circ$, Manual Adjust)
- POE; Alarm in/out
- IP66



IP66

Dimensions



Specifications		
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.5 lux@F1.2, AGC on, 0.1 lux@F1.2, AGC on, sens-up $\times 5$
	Shutter time	1/25s \sim 1/100,000s
	Lens	2.8 mm @F1.8 Angle of view: 81°
	Lens Mount	M12
	Adjustment Range	Pan: $\pm 15^\circ$, tilt: $0 \sim 90^\circ$, rotation: $\pm 15^\circ$
Compression Standard	Day& Night	Electronic
	Video Compression	H.264 / MPEG4 / MJPEG
	Bit Rate	32 Kbps \sim 16 Mbps
Image	Dual Stream	Yes
	Max. Image Resolution	1280x960
	Frame Rate	15 fps (1600 \times 1200), 25 fps (1280 \times 960), 30 fps (1280 \times 720)
	Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Security	User authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
	Mobile App	Guardian Expert for iPhone/iPad,/Android
Interface	Communication Interface	1 RJ45 10M / 100M ethernet interface
	Reset Button	Yes
General	Operating Conditions	$-10^\circ\text{C} \sim 60^\circ\text{C}$ ($14^\circ\text{F} \sim 140^\circ\text{F}$) humidity 95% or less (non-condensing)
	Power Supply	12 VDC \pm 10%, PoE (802.3af)
	Power Consumption	max. 4W
	Impact Protection	IEC60068-2-75Eh, 50J; EN50102, up to IK10
	Weather Proof	IP66
	IR Range	-
	Dimensions	99.9 \times 97.5 \times 46.5 mm (3.93" \times 3.84" \times 1.83")
	Weight	0.55lb (250g)