

CMIP3722 2 MegaPixel Dome IP Camera

Features

- 2 MP 1/3" CMOS Sensor
- 3.6mm Fixed Lens
- 1 IR Coated 4mm Lens
- Full HD 1080P (1920x1080)
- POE; 2-way Audio; Alarm in/out
- IP66



IP66

Specifications

Model	CMIP3722	
Image	Image Sensor	1/3" CMOS
	Effective Pixels	2.0 MegaPixels
	Frame Rate	50Hz: 1920x1080P@25fps 60Hz: 1920x1080P@30fps
	Bit Rate Range	Main bit rate: 200Kbps~8Mbps Sub bit rate: 100Kbps~6Mbps
	Video Compression	H.264 (Baseline profile) / MJPEG
Electrical	Video System	NTSC
	ICR	Yes
	Sync. System	Internal
	S/N Ratio	>54dB
	Minimum Illumination	0.1 Lux@F1.2; 0 Lux (LED ON)
Function	White Balance	ATW
	Multi-Streaming	YES
	Gain Control	Auto
	Masking	3 User Defined
	Net Protocol	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported
	Ethernet	1 Ethernet (10/100 Base-T) RJ45-Connector
	SD Card	IPV4/ IPV6 (DHCP/ Fixed) Support Micro SDHC, Mini SDHC with convertor
Infrared LED	Infrared Lamps	1 IR LED
	Effective IR Distance	20ft
Power	Input Voltage	DC 12V
Environment	Weather Protection	IP66
	Vandal Protection	Vandal-resistant
	Compliance	CE/ FCC/ RoSH Compliant/ IP66
	Operating Temperature	14°F ~ 122°F (-10°C ~ 50 °C)
	Storage Temperature	-4°F ~ 140 °F (-20°C ~ 60 °C)
	Humidity	85%RH Max. (Non-condensing)
Mechanical	Chasis Material & Color	Metal & White
	Product Dimension	3.9" (w) x 2.1" (h)
	Weight	

Dimensions

