

#### Features

- 2 MP 1/3" CMOS Sensor
- 2.7-9mm Varifocal Lens
- Auto Iris
- Day & Night (ICR)
- 18 IR LED@90ft
- POE; DC 12V
- IP66



#### Specifications

Model	CMIP3923	
<b>Camera</b>	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.5 lux @F1.2, AGC ON, 0 lux with IR 0.1 lux@F2.0, AGC ON, sens-up x 5, 0 lux with IR
	Shutter time	1/25s ~ 1/100,000s
	Lens	2.7 ~ 9mm @F1.2 Angle of view: 101° ~ 30.4°
	Lens Mount	Φ14
	Auto Iris	DC
<b>Compression Standard</b>	Video Compression	H.264 / MPEG4 / MJPEG
	Bit Rate	32 Kbps ~ 16 Mbps
<b>Image</b>	Max. Image Resolution	1600x1200
	Frame Rate	15 fps (1600 × 1200), 25 fps (1280 × 960), 30 fps (1280 × 720)
	Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
	BLC	Yes, zone configurable
<b>Network</b>	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Security	User authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
	Mobile App	Guardian Expert for iPhone/iPad,/Android
<b>Interface</b>	Communication Interface	1 RJ45 10M / 100M ethernet interface, 1 Vp-p composite output (75 Ω/RCA), Built-in Micro SD card slot up to 32 GB
<b>General</b>	Operating Conditions	-10 °C ~ 60 °C (14°F ~ 140 °F) humidity 95% or less (non-condensing)
	Power Supply	24 VAC ± 10%, PoE (802.3af)
	Power Consumption	max. 4.5W ~ 9W(IR LEDs +2W)
	Weather Proof	IP66
	IR Range	Up to 90ft
	Dimensions	Φ160 × 134.5 mm (Φ6.30" × 5.30")
	Weight	3.09lb (1400g)

#### Dimensions

