

Platinum **3** year warranty

Assured quality with a sterling warranty

CMIP5323-Z 2 MegaPixel Bullet IP Camera

Features

- 2 MP 1/3" CMOS Sensor
- 2.7-9mm Varifocal Lens (Motorized Varifocal)
- Auto Iris
- Day & Night (ICR)
- 48 IR LED@100ft
- POE; DC 12V
- IP66



IP66

Specifications

Model	CMIP5323-Z	
Image	Image Sensor	1/3" CMOS
	Effective Pixels	2 MegaPixel
	Frame Rate	1600 × 1200 @15fps, 1280 × 960 @25fps, 1280 × 720 @30fps
	Bit Rate Range	32Kbps~16Mbps
	Video Compression	H.264 (Baseline profile) /MPEG4/ MJPEG
Electrical	Video System	NTSC
	ICR	YES
	Sync. System	Internal
	S/N Ratio	-
Function	Minimum Illumination	0.5 lux @F1.2, AGC ON, 0 lux with IR 0.1 lux @F2.0, AGC ON,, sens-up x5, 0 lux with IR
	Electronic Shutter	1/25s ~1/100,000s
	Dual Streaming	YES
	Day&Night	Electronic
	BLC	YES
Network	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception
	Net Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Communication Interface	1 RJ45 10M / 100M ethernet interface
	Security	User Authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
Infrared LED	Infrared Lamps	48 IR
	Effective IR Distance	100 ft
Power	Power Supply	DC 12V, PoE (802.3af)
	Power Consumption	max. 9.5W
Environment	Impact Protection	-
	Weather Protection	IP66
	Compliance	-
	Operating Temperature	14°F ~ 122°F (-10°C ~ 50 °C)
	Storage Temperature	-4°F ~ 140 °F (-20°C ~ 60 °C)
Mechanical	Humidity	90%RH Max. (Non-condensing)
	Chasis Material & Color	Metal & White
	Product Dimension	3.86" (w) × 3.49" (h) × 12.94" (length-fully extended)
	Weight	3.75 lbs (1700g)

Dimensions

