

Features

- 2 MP 1/3" CMOS Sensor
- 2.7-9mm Varifocal Lens
- Auto Iris
- Day & Night (ICR)
- 48 IR LED@100ft
- POE; DC 12V
- IP66



Specifications

Model	CMIP5323	
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.5 lux@F1.2, AGC on 0.1 lux@F1.2, AGC on, sens-up × 5, 0 lux with IR
	Shutter time	1/25s ~ 1/100,000s
	Lens	2.7 ~ 9mm @F1.2 Angle of view: 101° ~ 30.4°
	Lens Mount	Φ14
	Auto Iris	DC drive
	Day& Night	IR cut filter with auto switch
Compression Standard	Video Compression	H.264 / MPEG4 / MJPEG
	Bit Rate	32 Kbps ~ 16 Mbps
Image	Max. Image Resolution	1600x1200
	Frame Rate	15 fps (1600 × 1200), 25 fps (1280 × 960), 30 fps (1280 × 720)
	Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
	BLC	Yes, zone configurable
Network	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Security	User authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
	Mobile App	Guardian Expert for iPhone/iPad,/Android
Interface	Communication Interface	1 RJ45 10M / 100M ethernet interface
	Operating Conditions	-10 °C ~ 60 °C (14°F ~ 140 °F) humidity 90% or less (non-condensing)
General	Power Supply	12 VDC ± 10%, PoE (802.3af)
	Power Consumption	max. 9.5W
	Weather Proof	IP66
	IR Range	Up to 100ft
	Dimensions	3.86" × 3.49" × 12.94"
	Weight	3.75lb (1700g)

Dimensions

