# **MULTI-TEST MONITOR**



PTZ CONTROL TEST RS-485 - PELCO-D/P PROTOCOL

# UTP CABLE TEST

WIRING CONDITION (SHORT/DISCONNECTED)

**DC 12V - 1A OUTPUT** 

SUPPLY POWER TO A CAMERA



**AUDIO TEST** CHECK AUDIO FUNCTION



# **RS-485 DATA TEST**

DISPLAYS HEX DATA FROM A DEVICE

### **DIGITAL MULTIMETER**

**VOLTAGE - CURRENT - RESISTANCE -CAPACITANCE - CONTINUITY - DIODE** 









- DC 9V / 2A power adapter included
- 1600mA eechargeable battery included Digital multi-meter

- AC/DC Voltage : 0~300V AC/DC Current : 400.0μA · 4000μA · 40.00mA · 400.0mA
- · 10A
- Resistance : 400.0Ω · 4.000K · 40.00K · 40.00K · 40.00K · 40.00M

- Capacitance : 4.00nF~400μF
- Continuity : <50Ω sound
- reminder

- Video in : BNC connector
- DC 5V 1.0A Power Supply Included Built-in rechargeable battery : 3.7V 2000mA/h Power out : DC 12V 400mA max
- 2 status LED

## **CONTENTS**

CARRYING CASE - HOLD STRAP - POWER SUPPLY -**CABLE - TESTER MONITOR - UTP TERMINATOR** 





**INTERNAL** RECHARGEABLE TO POWER UP **A CAMERA** 

**TEST** 

**UTP CABLE FOR SHORT** OR DISCONNECT





