



16 POE PORTS

Plus one additional gigabit uplink

100Mbps (1 Gigabit Uplink)

Data transfer rate

250W MAX POWER

30W max per port

IEEE 802.3af

Standard

16 DIP SWITCHES

Full power on/off control

POWER PROTECTION

OVP & OCP

UNMANAGED

Ports Automatically detect devices

19" RACK MOUNTABLE

Built-in

Standards

IEEE 802.3/u 10/100/1000Base/TX
IEEE 802.3x Flow Control
IEEE 802.3af PoE compliant
Midspan PoE compliant

Number of Ports

16 PoE ports + 1 gigabit uplink port

MAC Address

8k

Buffer Memory

512kb

Transmission Method

Store and Forward

Filtering/Forwarding Rates

1000Mbps port - 1,488,000pps
100Mbps port - 148,800pps
10Mbps port - 14,880pps

Transmission Media

10BaseT CAT 3, 4, 5 UTP
100/1000BaseTX CAT 5 UTP/STP

Max Power

250W (30W per port)

Output PoE Pin

4, 5, 7, 8

LED Indicators

Ports 1-16: 10/100Mbps, PoE on/off,
Power, Port 17: 10/100/1000Mbps

Power Adapter

Input: 100-240VAC, 50-60Hz
Output: 56VDC 3.6A (250W)

Dimensions H x W x D

18.9" x 4.6" x 1.6" (480 x 118 x 40mm)

Weight

4 lbs (1.8kg)

Operating Temperature

32°F ~ 122°F (0°C - 50°C)

Humidity

10 ~ 90% RH (Non-Condensing)

Certifications

FCC Class A, CE