

LTD2308ME-A 8 Channel High Performance DVR (ME-A Series)

Features

- Real-Time High Resolution Recording
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 2 Year Warranty & Free Life-Time Technical Support



Specifications

System	Compression Format	H.264
	OS	Embedded Linux
	Input	8CH, BNC (1.0Vp-p, 75Ω)
Video	VGA Output	1*VGA:1280x1024, 800x600, 1024x768
	BNC	1*BNC Mainout
	Loop Output	NO
	Spot Output	YES
	HDMI	Compatible with HDMI:1920x1080
Audio	Audio Input	4CH, RCA
	Audio Output	1CH, RCA
	Bidirectional Talk	YES
Recording	Real Time Recording	2CH D1 + 6CH CIF
	D1	60(NTSC)/50(PAL)fps
	CIF	240(NTSC)/200(PAL)fps
	Recording Mode	Schedule, Manual, Motion, Sensor
Playback	Playback Channel	8CH
	Search Mode	Time, Event, File Management, Snapshot
Backup	USB Disk	1 USB2.0 port for portable HDD
	DVD Burner	Optional
	Backup Format	DAT or AVI
Dual Steam	Master Stream	1~25/30fps@4CIF/CIF
	Network Stream	1~6/7fps@CIF
Remote Application	Browser	IE (windows XP/vista/7), Safari(Mac OS), Chrome, Firefox
	CMS	YES
	Mobile Phone OS	SuperCam/pro/HD for iPhone(iPad/iPad2)/Blackberry/Android
	User Access	10 users online with professional authority management
Alarm	Alarm Input	8 CH
	Alarm Output	1 CH
Storage	HDD (Each max. size 2 TB)	2x SATA, up to 4TB
	e-SATA	NO
	Max HDD after Deploying	1
	DVD Writable Driver	
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP, VISCA, SAMSUNG, RM110,HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
	Remote Control	1
Others	Power Supply	DC12V
	Operating Temperature	0°C ~50°C
	Humidity	10% ~ 90% Humidity
	Dimension	16.9"(L)×15"(W)×2"(H)

Front/Back View



LTD2316ME-A 16 Channel High Performance DVR (ME-A Series)

Features

- Real-Time High Resolution Recording
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 2 Year Warranty & Free Life-Time Technical Support



Specifications

System	Compression Format	H.264
	OS	Embedded Linux
Video	Input	16CH, BNC (1.0Vp-p, 75Ω)
	VGA Output	1*VGA:1280x1024, 800x600, 1024x768
	BNC	1*BNC Mainout
	Loop Output	NO
	Spot Output	YES
Audio	HDMI	Compatible with HDMI:1920x1080
	Audio Input	4CH, RCA
	Audio Output	1CH, RCA
Recording	Bidirectional Talk	YES
	Real Time Recording	2CH D1 + 14CH CIF
	D1	120(NTSC)/100(PAL)fps
	CIF	480(NTSC)/400(PAL)fps
Playback	Recording Mode	Schedule, Manual, Motion, Sensor
	Playback Channel	16CH
Backup	Search Mode	Time, Event, File Management, Snapshot
	USB Disk	1 USB2.0 port for portable HDD
	DVD Burner	Optional
Dual Steam	Backup Format	DAT or AVI
	Master Stream	1~25/30fps@4CIF/CIF
Remote Application	Network Stream	1~6/7fps@CIF
	Browser	IE (windows XP/vista/7), Safari(Mac OS), Chrome, Firefox
	CMS	YES
	Mobile Phone OS	SuperCam/pro/HD for iPhone(iPad/iPad2)/Blackberry/Android
Alarm	User Access	10 users online with professional authority management
	Alarm Input	16 CH
Storage	Alarm Output	1 CH
	HDD (Each max. size 2 TB)	2x SATA, up to 4TB
	e-SATA	NO
	Max HDD after Deploying DVD Writable Driver	1
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON,STAR,VIDO,DSCP, VISCA, SAMSUNG, RM110, HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
	Remote Control	1
Others	Power Supply	DC12V
	Operating Temperature	0°C ~50°C
	Humidity	10% ~ 90% Humidity
	Dimension	16.9"(L)×15"(W)×2"(H)

Front/Back View

