

LTD2316SE-C



Key features

- H.264 video compression
- Support WD1 recording
- 16-ch D1 resolution realtime recording
- HDMI output at up to 1920×1080 resolution
- Dual-stream
- 16-ch synchronous playback
- 16-ch/1-ch Alarm input/output,4-ch/1-ch Audio input/output
- Mobile Phone Surveillance(IPhone, Ipad, Android phone,Windows 7 phone)
- HDD quota and group management
- DC 12V input

Rear Panel of LTD2316SE-C



1. Audio in
2. Video in
3. Audio out
4. Video out
5. HDMI interface
6. VGA interface
7. Spot
8. Alarm/PTZ
9. LAN network interface
10. USB interface
11. Power input,DC 12V
12. Power switch

LTD2316SE-C	
Video / Audio input	
Video compression	H.264
Video input	16-ch
Video input interface	BNC (1.0 Vp-p, 75Ω)
Audio compression	G.711u
Audio input	4-ch, RCA(2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Video / Audio output	
HDMI output	1-ch, resolution: 1080P:1920×1080 /60 Hz
VGA output	1-ch, resolution: 1280×1024 /60 Hz,1024×768/60HZ,800×600/60HZ
CVBS output	1-ch, BNC (1.0 Vp-p, 75Ω), resolution: NTSC: 704 × 480,PAL: 704 × 576
Video spot out	1-ch, BNC (1.0 Vp-p, 75Ω), resolution: NTSC: 704 × 480,PAL: 704 × 576
Encoding resolution	WD1:240(NTSC)/192(PAL)fps;D1:480(NTSC)/400(PAL)fps;CIF:480(NTSC)/400(PAL)fps
Video bit rate	32 Kbps ~ 3072 Kbps, or user defined (max. 3072 Kbps)
Audio output	1-ch, RCA (linear, 1KΩ)
Audio bit rate	64 Kbps
Dual-stream	Support; Sub-stream: CIF
Synchronous playback	16-ch
Hard disk	
SATA	1 SATA interfaces
Capacity	Up to 3TB
External interface	
Network interface	1, RJ45 10M / 100M / 1000M Ethernet interface
PTZ interface	RS-485(half-duplex)
USB interface	2, USB2.0
Alarm in	16
Alarm out	1
General	
Power supply	DC 12V 2A
Consumption	≤ 10 W(without hard disk or DVD-R/W)
Working temperature	-10 ° C ~ + 55 ° C(14 ° F - 122 ° F)
Working humidity	10% ~ 90%
Chassis	Small 1U chassis
Dimensions(W x D x H)	300 × 270 × 58mm (11.8"×10.6"×2.3")
Weight	≤ 2kg (4.4lb)(without hard disk or DVD-R/W)