

Platinum HD TVI 8CH DVR LTD2708TE-M



Key Features:

- 8CH HD TVI video input
- 8CH 1080P@15fps or 720p@ 30fps live preview
- 8CH 1080P@ 15fps or 720P@ 30fps recording
- 8 CH simultaneously playback

Rear Panel:

- | | |
|------------------|------------------|
| 1. Audio Out | 6. LAN |
| 2. Audio In | 7. USB Interface |
| 3. Video In | 8. DC 12V |
| 4. HDMI | 9. RS-485 Serial |
| 5. VGA Interface | |



Platinum HD TVI 8CH DVR

LTD2708TE-M

VIDEO/ AUDIO INPUT	
Video compression	H.264
Video input	8ch BNC (1.0 Vp-p, 75 Ω), PAL / NTSC self-adaptive
IP input	up to 4ch
Audio compression	G.711u
Audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ)
VIDEO/ AUDIO OUTPUT	
HDMI/ VGA output	1920 × 1080
Encoding resolution	1080P: 15fps(NTSC)/12fps(PAL) 720P:30fps(NTSC)/25fps(PAL)
Frame rate	1080P: 100fps(PAL)/120fps(NTSC) 720P/WD1/D1: : 200(PAL)/240(NTSC)
Video bit rate	1MKbps-4 Mbps
Audio output	1-ch, RCA (Linear, 1 kΩ)
Audio bit rate	64 Kbps
Dual-stream	Support
Stream type	Video, Video & Audio
Synchronous playback	8ch
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
NETWORK	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
HARD DISK	
SATA	2 SATA
Capacity	Up to 3TB capacity for each disk
EXTERNAL INTERFACE	
Network interface	1:10M / 100M/1000M self-adaptive Ethernet interface
Serial interface	RS-485, Keyboard
USB port	2 × USB2.0
Alarm in/ out	-
GENERAL	
Power supply	DC12V
Consumtion	≤ 14W
Working temperature	-10 ° C ~ +50 ° C(14° F - 122° F)
Working humidity	10% ~ 90%
Chassis	1U chassis
Dimensions (WxDxH)	430 × 300 × 55 mm (16.9 × 11.8 × 2.2 inch)
Weight	≤ 3Kg (6.6lb)