

LTD6104C DVR with 10" Swivel Monitor

Features

- Standard 4 CH H.264 Pentaplex Network DVR
- Pentaplex mode: recording, playback, setup, backup, network and mobile phone surveillance simultaneously
- CIF Realtime recording; D1 recording supported
- Full channel CIF simultaneously playback with 1 ch audio
- Various recording mode: schedule, Motion, Sensor
- Various searching mode: Time, Event(Alarm, Motion Detection), Recording List
- Strong log, privacy mask
- Powerful remote surveillance, playback, recording, control, menu setup, recording backup
- Flexible Display mode : Auto Switch, Full Screen, Quad, etc
- Support VGA output, display resolution adjustable up to 1024*768



Specifications

System	Compression Format	H.264
	OS	Embedded Linux
Video	Input	BNC x 4CH, CVBS 1.0Vpp 75Ω
	VGA Output	1*VGA, 1024x768, 800x600
	BNC	1*BNC Mainout
	Loop Output	No
	Spot Output	No
	HDMI	No
	Audio	Audio Input
Audio Output		RCA x 1CH
Bidirectional Talk		No
Recording	Real Time Recording	4CH CIF real time
	D1	30(NTSC)/25(PAL)fps
	CIF	120(NTSC)/100(PAL)fps
	Recording Mode	Schedule, Motion, Sensor
Playback	Playback Channel	4CH
	Search Mode	Time, Event, File Management
Backup	USB Disk	2 USB2.0 port
	DVD Burner	No
	Backup Format	H.264
Remote Application	Browser	IE (windows XP/vista/7)
	Mobile Phone OS	MEye for iPad/iPad2/iPhone/ Blackberry/ Android
	User Access	admin/guest
Alarm	Alarm Input	N/A
	Alarm Output	N/A
Storage	HDD (Each max. size 2 TB)	1SATA
	e-SATA	No
	Max HDD after Deploying DVD Writable Driver	-
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCO P, PELCO D, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	PTZ Control	pan, tilt, zoom, preset, cruise
Network	Ethernet Protocol	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, SMTP
Others	Remote Control	1
	Power Supply	DC 15V/3A
	Operating Temperature	0°C ~ 55°C
	Humidity	20% ~ 95% humidity
	Dimensions	245mm x 270mm x 46mm

Back View

