

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V



1/2" 8 Megapixel progressive CMOS • H.265 & H.264 dual-stream encoding • 25/30fps@8MP(3840×2160)
• WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer,
CMS(DSS/PSS) & DMSS • Micro SD card slot, up to 128GB • Motorized 3.7~11mm varifocal lens • Max IR
LEDs Length 60m • IP67, IK10(optional) • PoE

Overview

The IR Megapixel Vari-focal camera delivers with a 3.7~11mm varifocal lens. The camera's elegant blend of

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V

aesthetics combined with a range of easy mounting solutions provides an excellent choice for a variety of small to mid-size applications at an affordable price.

FEATURES

- **Smart Codec (H.265+ & H.264+):** Smart Codec is the optimized implementation of standard video compression (H.265 & H.264) that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart Codec technology reduces bit rate and storage requirements by up to 70% when compared to the standard video compression.
- **4K Technology:** 4K technology as a revolutionary breakthrough in image, which enhance the expressive image of essence, allowing users to experience the best picture quality brought about by the visual feast . For the purposes of 4K surveillance with four times the 1080P resolution, presented to the user with more details . Under the same scenario by raising the pixels , reduce the camera cost.
- **Protection:** Supporting $\pm 30\%$ input voltage tolerance, this camera suits even the most unstable conditions for outdoor applications. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.
- **Intelligent Video Analysis (IVS):** Eyemax camera is equipped with a built-in intelligent analytic algorithm based on video, which can realize intelligent functions like Tripwire and Intrusion, to quickly and accurately respond to monitoring events in specific area, It can enhance monitoring efficiency. In addition, the camera supports intelligent tamper detection, which is to generate warning message via detecting dramatic scene change and to guarantee effective video surveillance.
- **Wide Dynamic Range (WDR):** The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, true WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.
- **Smart IR Technology:** With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 60m (197ft).
- **Protection (IP67, wide voltage):** The camera allows for $\pm 25\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) , the camera is the choice for installation in even the most unforgiving environments.
- **Environmental:** Eyemax cameras operate in extreme temperature environments, rated for use in

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V

temperatures from -30° C to +60° C (-22° F to +140° F) with 95% humidity.

- **Interoperability:** The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

SPECIFICATIONS

Camera	
Image Sensor	1/2" 8 Megapixel progressive CMOS
Effective Pixels	3840(H)×2160(V)
RAM/ROM	512MB / 128MB
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual, 1/3 ~ 1/100,000s
Minimum Illumination	0.004Lux / F1.9 (Color, 1/3s, 30IRE) 0.09Lux / F1.9 (Color, 1/30s, 30IRE) 0Lux / F1.9 (IR on)
S/N Ratio	More than 50dB
IR Distance	Distance up to 60m (197ft)
IR On/Off Control	Auto / Manual
IR LEDs	4
Lens	
Lens Type	Motorized
Mount Type	Board-in
Focal Length	3.7 ~ 11mm
Max. Aperture	F1.9
Angle of View	H:112° ~ 46° V:60° ~ 26°
Focus Control	Fixed
Close Focus Distance	0.2m(0.66ft)
Dori Distance	
Wide	Detect: 83m(272ft) Observe: 33m(108ft) Recognize: 17m(56ft) Identify: 8m(26ft)

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V

Tele	Detect: 190m(623ft) Observe: 76m(249t) Recognize: 38m(125ft) Identify: 19m(62ft)
Pan/Tilt/Rotation	
Pan/Tilt/Rotation Range	Pan:0° ~ 355° / Tilt:0° ~ 75° / Rotation:0° ~ 355°
Intelligence	
Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal access, Storage anomaly
IVS	Tripwire, Intrusion
Video	
Compression	H.265+ / H.265 / H.264+ / H.264
Smart Codec	Support H.265+ / H.264+
Streaming Capability	2 Streams
Resolution	4K(3840 × 2160) • 6M(3072 × 2048) • 5M(2560 × 1920) • 3M(2048 × 1536) • 3M(2304 × 1296) • 1080P(1920 × 1080) • 1.3M(1280 × 960) • 720P(1280 × 720) • D1(704 × 576 • 704 × 480) • VGA(640 × 480) • CIF(352 × 288 • 352 × 240)
Frame Rate	
Frame Rate	Main Stream: 4K (1 ~ 25/30fps) Sub Stream: D1(25/30Fps)
Bit Rate Control	CBR / VBR
Bit Rate	H.264: 32Kbps~8192Kbps / H.265: 16Kbps~8192Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto / Natural / Street Lamp / Outdoor / Manual
Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Digital Zoom	16x

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V

Flip	0° / 90° / 180° / 270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)
Audio	
Compression	G.711a / G.711Mu / AAC / G.726
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	10 Users / 20 Users
Edge Storage	NAS, Local PC for instant recording, Mirco SD card supports up to 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Certifications	
Certifications	CE (EN 60950:2000) UL:UL60950 ~ 1 FCC: FCC Part 15 Subpart B
Interface	
Video Interface	N/A
Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	1 channel In: 5mA 5VDC 1 channel Out: 300mA 12VDC
Electrical	
Power Supply	DC12V PoE (802.3af)(Class 0)
Power Consumption	<14.3W
Environmental	

EYEMAX | 4K(8MP) H.265+ Outdoor IR Bullet Network Camera, Starlight, True-WDR, Motorized 3.7-11mm, UL-Listed , IR Range up to 197ft, IP67, IK10, PoE or DC 12V

Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	IK10
Construction	
Casing	Metal
Dimensions	244.1mm × 79mm × 75.9mm (9.61" × 3.11" × 2.99")
Net Weight	0.824Kg (1.82lb)
Gross Weight	1.09Kg(2.4lb)