

IP NVR / 12MP / 16 CH / 160Mbps / 2xSATA / 16Ch PoE / H.264+ / HDMI / VGA



Up to 16Ch. IP cameras input • 160 Mbps Bit rate input Max and 160 Mbps Bit rate Output Max • Third-party network cameras supported • Up to 12MP resolution recording • Independent VGA and HDMI output • VGA output up to 1080p@60Hz • HDMI output up to 4K@30Hz • 2 SATA HDD interface up to 6TB each

SPECIFICATIONS

Video Compression	H.265 / H.264 / H.264+ / MJPEG
IP Video Input	16 ch, (160 Mbps max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-Way Audio	1/1
Real-time Recording Resolution	Up to 12 megapixel
HDMI Output Resolution	4K, 3840×2160@30Hz, - 2K, 1920×1080@60Hz, 1600×1200@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz

IP NVR / 12MP / 16 CH / 160Mbps / 2xSATA / 16Ch PoE / H.264+ / HDMI / VGA

VGA Output Resolution	1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
Synchronous Playback	2 Ch. @ 4K, or 8 Ch. @ 1080p, 16 Ch. @ 720p
Alarm I/O	4/1
Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet Interface
PoE Network Interface/Built-in Switch	16 independent 10/100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces(up to 6TB each)
USB interface	1 x USB2.0, 1 x USB3.0
Operation Temperature	12F ~ 131F +
Chassis	385mm chasis
Dimension(W x D x H)	15.2 x 12.4 x 2.0
Power Supply	100 ~ 240VAC, 15W
Weight	6.6lb (without hard disk)