




\*Rear Panel

# IP CAMERAS **32CH** NETWORK VIDEO RECORDER

D1 / 22CH 720p / 22CH 1080p • 1xHDMI • 1xVGA • 1xBNC • ONVIF Version 2.0/2.1/2.2 Conformance



**SECURITY IN YOUR HAND**  
Multi-Channel Remote Live View

## FEATURES

- Up to 32CH with D1 / 22CH with 720p / 22CH with 1080p Realtime Live View
- H.264/MPEG-4 Dual Codec Decoding
- Up to 5MP Resolution
- HDMI / VGA / BNC Simultaneous Video Output
- 16 Channel Synchronous Realtime Playback
- ONVIF Version 2.0/2.1/2.2 Conformance
- Support 2 SATA HDDs up to 3TB
- Multiple Network Monitoring: Web Viewer, CMS & Mobile



\*Accessories

NVST SR532	
<b>SYSTEM</b>	
Operating System	Embedded LINUX
<b>VIDEO &amp; AUDIO</b>	
IP Camera Input	32 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, BNC
<b>DISPLAY</b>	
Interface	1 HDMI, 1 VGA, 1 BNC
Resolution	800×600;1024×768;1280×1024;1440×900;1920×1080
Display Split	1/4/9/16/32
OSD	Camera Title, Time, Video Loss, Camera Lock, Motion Detection, Recording
<b>RECORDING</b>	
Compression	H.264 (High Profile@Level4.2) / MPEG-4
Resolution	5MP(2560×1920) / 3MP(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	Max 22CH@1080P or 22CH@720P or 32CH@D1
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
<b>VIDEO DETECTION &amp; ALARM</b>	
Trigger Events	Recording, Alarm, Video Push, Email, Buzzer
Video Detection	Motion Detection, Video Loss, HDD Loss
Alarm Input	16 Channel
Relay Output	3 Channel
<b>PLAYBACK &amp; BACKUP</b>	
Sync Playback	1 / 4 / 8 / 16
Search Mode	Time/Date, Alarm, MD & Exact Search (Accurate to second)
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device / Network
<b>NETWORK</b>	
Ethernet	RJ-45 port (10/100M/1000M)
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, DHCP, DNS, PPPOE, DDNS
Max. User Access	10 Users
Mobile Phone	IPhone, IPad, Android
<b>STORAGE</b>	
Internal HDD	4 SATA Ports, up to 3TB
<b>AUXILIARY INTERFACE</b>	
USB Interface	3 Ports (1 Rear), USB2.0
RS232	Yes
RS485	1 Port, For PTZ Control
<b>GENERAL</b>	
Power Supply	NVR:DC12V/4A
Power Consumption	20W(without HDD)
Working Environment	-10 ~+55 °C / 10~90%RH / 86~106kpa
Dimension(W×D×H)	1U,375×378×65(mm)