

TS series 5416-16E | 16Ch Network Video Recorder (NVR), 16 PoE port, H.265, up to 8MP (4K), HDMI, 112Mbps Bandwidth, 8 × SATA, 1 × eSATA



16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P high definition PoE NVRs, which adopt the most advanced SOC technique to ensure high definition recording in each channel and realize outstanding robustness of the system. It integrates with 16 PoE network ports, support 16 CH IPC direct connection to NVR , simultaneous 16 CH playback, and 4K high definition display. The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.

FEATURES

- Support 16 CH 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion / sensor
- Playback : 16 CH simultaneous playback

TS series 5416-16E | 16Ch Network Video Recorder (NVR), 16 PoE port, H.265, up to 8MP (4K), HDMI, 112Mbps Bandwidth, 8 × SATA, 1 × eSATA

- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- 16 PoE network ports, support IPC direct connection to NVR; support PoE power supply
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log view and device status view
- 4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS

SPECIFICATIONS

System	
Compression	Standard H.265, H.264
OS	Embedded Linux
Video	
Network Input	16 CH IPC input
Network Access Bandwidth	112Mbps
Network Access Format	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P@25 / 30fps
Output	HDMI × 1 : 3840 × 2160 / 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768
Audio	
Network Input	16 CH IPC audio input
2-way Audio	RCA × 1
Local Output	RCA × 1
Record	
Record Stream	Dual stream recording
Resolution	8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P

TS series 5416-16E | 16Ch Network Video Recorder (NVR), 16 PoE port, H.265, up to 8MP (4K), HDMI, 112Mbps Bandwidth, 8 × SATA, 1 × eSATA

Mode	Manual, timer, motion, sensor
Playback	
Simultaneous Playback	Max 16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
Alarm	
Mode	Manual, sensor, motion, exception
Input	Support IPC alarm input
Output	Support IPC alarm output
Triggering	Record, snap, preset, e-mail, etc.
Network	
Interface	RJ45 10 / 100 / 1000 Mbps × 1
PoE Port	RJ45 × 16
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP
Mobile Device	
OS	iOS, Andriod
Storage	
HDD	SATA × 2, max 8T per HDD
Backup	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
Port	
USB	USB 2.0 × 2 (one in the front panel and the other in the rear panel)
Remote Controller	Optional
Others	
Power Supply	DC48V
Consumption	≤ 15W (without HDD)
Dimensions (mm)	380 × 268 × 52 (W × D × H)

TS series 5416-16E | 16Ch Network Video Recorder (NVR), 16 PoE port, H.265, up to 8MP (4K), HDMI, 112Mbps Bandwidth, 8 × SATA, 1 × eSATA

Work Environment	-10 ~ 50°C, 10% ~ 90% humidity
------------------	--------------------------------