

HDTV

1080P IR DOME CAMERA



TDR 2544V-B Black
TDR 2544V-W White

- 2.8~12mm Auto-Iris Vari-Focal Lens
- True Day & Night (ICR)
- DC 12V / AC 24V

ANTI-IR REFLECTION SERIES

PREVENTS WASHED OUT VIDEO CAUSED BY IR REFLECTION FROM OBSTACLES (WATER OR OIL) ON COVER

4 PCS OF HIGH POWERED IR

SEE MUCH DETAILS IN A GREAT DISTANCE

SMART IR

PREVENTS WASHED OUT IMAGE CAUSED BY INTENSE IR LIGHT AT A CLOSE RANGE

ANTI-IR REFLECTION CAMERA

COMPETITOR'S DOME CAMERA



FEATURES

- HD-TVI : High Definition Transport Video Interface
1080p FULL HD Flawless Video
- **Anti-IR Reflection Series** : (The Shield) : Prevents washed out video caused by IR reflection from obstacles (water or oil) on cover (China Patent: 201430447051.X / 201430489022.X / 201430488715.7 / 2014305487734)
- **4 High Powered IR LED** :
Up to 50% more brighter than conventional IR LED
- **SUPERDOME®** Series Camera with easy flip cover open (US Patent : 8337100)
- **4-Axis Construction** : By adjusting '4-Axis' control, you get a straight view regardless whether the camera is installed on a wall or ceiling
- 1/2.9 inch Sony CMOS : Low Power Consumption
- Minimum Illumination - 0 Lux with IR on
- 2.8~12mm Auto-Iris **IR Corrected** Lens Installed - provides the best focused image both color & IR mode
- Auto Removable IR-Cut Filter (ICR) : True Day & Night. Deep color and clear video at both day and night time
- OSD (On Screen Display) - Easy Camera Setup
- DNR (Digital Noise Reduction)
- WDR (Wide Dynamic Range)
- AWB (Auto White Balance) / Sens-Up (x2~x8)
- DC 12V / AC 24V Dual Power

TDR 2544V	
Resolution	1080p, 720p, 720p CROP
Sensor	1/2.9 inch Sony CMOS
Total Pixels	2000(H) × 1241(V) = 2,482,000
Effective Pixels	1944(H) × 1092(V) = 2,122,648
Scanning System	Progressive
S/N (Y Signal)	More than 52 dB (AGC Off)
Video Output	TVI / CVBS: 1.0Vp-p (75ohm)
Min. Illumination	0 Lux at IR On
White Balance	Auto / Auto Ext / Preset / Manual
Shutter	Auto / Manual (1/30sec ~ 1/60,000sec)
Brightness	Adjustable (0~20 Step)
Sens Up	OFF / X2 / X3 / X4 / X5 / X6 / X7 / X8
DNR	OFF / Low / Middle / High
Backlight	OFF / WDR / BLC / HLM
ACE	OFF / Low / Middle / High
Day & Night	Auto (Day <-> Night Time Change), Color, B/W, Extern, MDIR (Search Option)
Privacy	OFF / ON (16 Zone)
Motion	OFF / SET
Digital Zoom	0~127
Flip	OFF / ON
Freeze	OFF / ON
Language	English, Chinese, Chinese(S), Japanese, Korean
Sharpness	Adjustable (0~10 Step)
Defog	OFF / SET
Communication Port	RS-485 (Pelco-D)
Smart IR	Adjustable (0~20 Step)
Operating Temp / Humidity	-10°C ~ +50°C(14°F ~ 122°F) / 30%~80% RH
Storage Temp / Humidity	-20°C ~ +60°C(-4°F ~ 140°F) / 20%~90% RH
Power	DC 12V / AC 24V Dual Power
Signal Transmission	The distant difference is occurred according to cable option and other circumstances. (Coaxial Cable 300M)

MADE IN KOREA

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.