

HD-TVI 4MP Outdoor IR Bullet Camera with Vari-Focal Lens, 6 COB IR, IP68, Dual Power



1/2.9 inch SONY CMOS (IMX-326) • Upgraded Waterproof Housing (IP 68 rating) • High Definition Serial Digital Interface • 0 Lux at IR On (IR06) • WDR (Wide Dynamic Range) • DNR (Digital Noise Reduction) • Day & Night • ICR V/F lens, DC Auto IRIS V/F Lens, DC Auto IRIS & TDN V/F Lens • Focal Length : 2.8~12mm

SPECIFICATIONS

| | |
|------------------|--------------------------------|
| Resolution | 1440P, 1080P, 720P |
| Sensor | 1/2.9 inch SONY CMOS (IMX-326) |
| Total Pixels | 3096(H) × 2218(V) = 6.87M |
| Scanning System | PROGRESSIVE |
| S/N (Y signal) | More than 52 dB (AGC Off) |
| Video Output | TVI, CVBS: 1.0Vp-p (75ohm) |
| Min.Illumination | 0 Lux at IR On |

HD-TVI 4MP Outdoor IR Bullet Camera with Vari-Focal Lens, 6 COB IR, IP68, Dual Power

| | |
|--------------------------|--|
| White Balance | AUTO / AUTO EXT / PRESET / MANUAL |
| Electronic shutter speed | AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER |
| Brightness | ADJUSTABLE (0 ~ 20 STEP) |
| DNR | OFF / LOW / MIDDLE / HIGH |
| BACKLIGHT | OFF / WDR / BLC / HLC |
| Day & Night | AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN |
| PRIVACY / MOTION | OFF / ON |
| Language | ENG, CHN, CHN(S), JPN, KOR |
| Sharpness | ADJUSTABLE (0 ~ 10 STEP) |
| COMM. | RS-485(PELCO-D) |
| Temperature/Humidity | Operating (14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH) Storage (-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH) |
| Power | AC 24V / DC 12V Dual Power |