

Magic G5342 | 5MP 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 65ft (20m) IR Range, UTC, DC 12V, Vandal-resistant



5 MP High Performance CMOS • Up to 2560 × 1944 Resolution • 2.8 / 3.6 mm Fixed Lens Options • 3D DNR, DWDR • EXIR 2.0 up to 65 ft (20 m) IR Range • Multiprotocol Output: TVI / AHD / CVI / CVBS • Up-the-Coax • IP67, IK10 Protection

5 MP Outdoor Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video. EXIR 2.0 is proprietary IR extended range technology, which has a range of 65 feet (20 meters). The 2.8 / 3.6 mm fixed lens options are optimized for viewing angles that fit any situation. DWDR (Digital Wide

Magic G5342 | 5MP 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 65ft (20m) IR Range, UTC, DC 12V, Vandal-resistant

Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

FEATURES

- 5 MP High Performance CMOS
- Up to 2560 × 1944 Resolution
- 2.8 / 3.6 mm Fixed Lens Options
- 3D DNR, DWDR
- EXIR 2.0 up to 65 ft (20 m) IR Range
- Multiprotocol Output: TVI / AHD / CVI / CVBS
- Up-the-Coax
- IP67, IK10 Protection

SPECIFICATIONS

Camera	
Image Sensor	5 MP progressive scan CMOS
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux @ (f 1.2, AGC on), 0 Lux with IR
Shutter Speed	1/30 s to 1/50,000 s
Lens	2.8 / 3.6 mm fixed lens options
Horizontal Field of View	85.5° (2.8 mm), 80.1° (3.6 mm)
Lens Mount	M12
Day/Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°; tilt: 0° to 75°; rotate: 0° to 355°
Synchronization	Internal synchronization
Frame Rate	5 MP @ 20 fps, 4 MP @ 30 fps, 1080p @ 30 fps
Menu	
AGC	Supported
Day / Night Mode	Auto / Color / BW (black and white)
White Balance	ATW/MWB

Magic G5342 | 5MP 4-in-1 Outdoor IR Dome Camera, IP67, Metal Body, Fixed Lens, 65ft (20m) IR Range, UTC, DC 12V, Vandal-resistant

BLC	Yes
DWDR	Yes
Language	English
Functions	Brightness, sharpness, DNR, mirror, Smart IR
Interface	
TVI Video Output	1 HD analog output
Switch Button	TVI / AHD / CVI / CVBS
General	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 4.3 W
Protection Level	IP67, IK10
Material	Metal
IR Range	Up to 65 ft (20 m)
Communication	Up-the-Coax
Dimensions	Ø 4.4" x 3.2" (Ø 111 mm x 82.4 mm)
Weight	Approximately 0.77 lbs (350 g)