

AR Series - 4CH Quad-brid DVR System supports 3MP/5MP HD-TVI



Quad-brid 1080p • 3MP • 5MP 4 CH

Supports HD-TVI / AHD / IP / 960H Analog cameras • Records up to 2 IP cameras • REAL-TIME Live • 12fps recording at 5MP and 15fps recording at 1080P • iPhone® Android® App Available (Guarding Expert) • Dual Streaming • RS-485 for PTZ control • Free DDNS Support • EZVIZ Cloud P2P • 1 x SATA (up to 6TB; 6TB EA.)
 Please use the link [HERE](#) to add HDD to cart.

KEY FEATURES




- 4 Ch Video & 4 Ch audio input
- HD-TVI / AHD / IP / Analog Quad-brid
- 12fps recording at 5MP and 15fps recording at 3MP
- Full channel recoding at 1080P resolution
- HDMI output at up to 1920x1080P resolution
- Support CVBS output
- Long transmission distance over coax cable
- Front panel and alarm I/O
- 1xSATA, 2 USB 2.0

SPECIFICATIONS

| Video / Audio Input | |
|----------------------|--|
| Video Input | 4Ch BNC interface (1.0Vp-p, 75Ω), supporting coaxitron connection |
| Supported HDTV input | 1080p/25Hz, 1080p/30Hz, 720p/25Hz, 720p/30Hz, 720P/50Hz, 720p/60Hz, 3MP, 5MP |
| Supported AHD input | 720p/25Hz, 720p/30Hz |
| CVBS input | Support |
| IP video input | 2-ch Up to 4.0 MP resolution |
| Audio compression | G.711u |
| Audio input | 4-ch, RCA (2.0 Vp-p, 1 KΩ) |

| Video/Audio output | |
|---------------------------|---|
| CVBS output | Support |
| HDMI/VGA output | VGA: 1-ch, 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz HDMI: 1-ch, 1920×1080/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz |
| Encoding resolution | 5MP@12fps/3MP@15fps/1080p/720p/WD1/4CIF/VGA/CIF |
| Frame rate | Main stream: 25 fps (P)/30 fps (N) |
| | Sub-stream: WD1/4CIF@12fps (non-real-time); CIF/QVGA/QCIF (real time) |
| Video bitrate | 32 Kbps to 10 Mbps |
| Audio output | 1-ch, RCA (Linear, 1 KΩ) |
| Audio bit rate | 64 Kbps |
| Dual-stream | Support |
| Stream type | Video, Video & Audio |
| Synchronous playback | 4-ch |
| Network management | |
| Remote connections | 128 |
| Network protocols | TCP/IP, PPPoE, DHCP, Hik-connect Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF |
| Hard disk | |
| SATA | 1 SATA interface |
| Capacity | Up to 6TB capacity |
| External Interface | |
| Two-way audio input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the audio input) |
| Network interface | 1, RJ45 10M/100M selfadaptive / Ethernet interface |
| USB interface | 2×USB 2.0 |
| Serial interface | 1; RS-485 serial interface, half-duplex |
| Alarm in/out | 4/1 |
| General | |
| Power supply | 12 VDC |
| Consumption (without HDD) | 15W |
| Working temperature | -10 °C to +55 °C (14 °F to 131 °F) |
| Working humidity | 10% to 90% |
| Dimensions (W × D × H) | 380×320×48 mm (15.0×12.6×1.9 inch) |
| Weight (without HDD) | 1.5 kg (3.3 lb) |

Contents



Smartphone Apps



Guarding Expert
for iPhone



Guarding Expert
for Android