

8CH PHD SERIES



- 720p@240fps Playback
- Dual Streaming
- H.264 / DC 12V

Automatically Detects HD-TVI & Analog & 960H Cameras



REAR PANEL


FREE
DDNS SERVICE

HDMI
OUTPUT

FEATURES

- H.264 & Dual-Stream Video Compression
- Support HD-TVI/Analog/IP Camera Triple Hybrid
- Support both HD-TVI & Analog cameras with adaptive access
- Full Channel@720P Resolution Real-Time Recording
- HDMI & VGA Output at up to 1920×1080P Resolution
- Long transmission distance over coax cable
- Support up to 16Ch Synchronous Playback at 1080P Resolution

ACCESSORIES



**SMART
PHONE
COMPATIBLE**

Guarding Expert



TVST PHD-08T

VIDEO/AUDIO INPUT	
Video Compression	H.264
Analog & HD-TVI Video Input	8Ch / BNC Interface (1.0Vp-p, 75Ω)
Supported Camera Types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Audio Compression	G.711u
Audio Input/Two-way Audio In	1-ch, RCA (2.0 Vp-p, 1 KΩ)
VIDEO/AUDIO OUTPUT	
HDMI/VGA Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding Resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video Bitrate	32 Kbps-6 Mbps
Audio Output	1-ch, RCA (Linear, 1KΩ)
Audio Bitrate	64 Kbps
Dual Stream	Support
Stream Type	Video, Video & Audio
Synchronous Playback	8Ch
Playback Resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
NETWORK MANAGEMENT	
Remote Connections	128
Network Protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
HARD DISK	
SATA	1 SATA Interface
Capacity	Up to 4 TB capacity for each disk
EXTERNAL INTERFACE	
Network Interface	1; 10M / 100M self-adaptive Ethernet interface
Serial Interface	1; standard RS-485 serial interface, half-duplex
USB Port	2 x USB 2.0
GENERAL	
Power Supply	12V DC
Consumption (without hard disks)	≤ 20W
Working Temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working Humidity	10%~90%
Chassis	1U chassis
Dimensions (W x D x H)	315 × 242 × 45mm (12.4 × 9.5 × 1.8 inch)
Weight (without hard disks)	≤ 1.5kg (3.3lb)

HDD INSTALLATION AVAILABLE UPON REQUEST
IR REMOTE & MOUSE INCLUDED

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.