

16CH STI SERIES



STI Series DVR accepts ANALOG / 960H / IP CAMERA



- REAL-TIME Live / 1/16fps to REAL-TIME Frame Rate
- H.264 / Dual Streaming
- RS-485 for PTZ control
- Free DDNS Support / EZVIZ Cloud P2P
- Manufactured by Hikvision



REAR PANEL

FEATURES

- Connectable to HD-TVI and analog cameras
- Connectable to the Coaxitron camera with long transmission distance
- Connectable to network cameras
- Simultaneous HDMI and VGA outputs at up to 1920x1080P resolution
- New GUI and support starting record with one key
- Redundant recording and holiday recording
- Instant playback for assigned camera during multi-channel live view mode
- Support up to 16-ch synchronous playback at 1080P resolution; and reverse playback for multi-camera
- Smart playback to go through less effective information
- Manual video quality diagnostics
- Customization of tags, searching & playing back by tags
- Locking and unlocking record files
- Support HDD quota and group management; different capacity can be assigned to different cameras under quota mode
- Provide up to 2 SATA interfaces for recording
- Up to 1 self-adaptive 10M/100M/1000M network interface
- Support access by EZVIZ Cloud P2P
- Support Hikvision DDNS (Dynamic Domain Name System)
- Network detection function.

TVST STI716	
VIDEO/AUDIO INPUT	
Video Compression	H.264
Analog & HD-TVI Video Input	16Ch / BNC Interface (1.0Vp-p, 75Ω)
Supported Camera Types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
IP Video Input	2Ch Up to 2.0MP Resolution
Audio Compression	G.711u
Audio Input/Two-way Audio In	1-ch, RCA (2.0 Vp-p, 1 KΩ)
VIDEO/AUDIO OUTPUT	
HDMI/VGA Output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding Resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video Bitrate	32 Kbps-6 Mbps
Audio Output	1-ch, RCA (Linear, 1KΩ)
Audio Bitrate	64 Kbps
Dual Stream	Support
Stream Type	Video, Video & Audio
Synchronous Playback	16Ch
Playback Resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
NETWORK MANAGEMENT	
Remote Connections	128
Network Protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
HARD DISK	
SATA	2 SATA Interface
Capacity	Up to 6TB capacity for each disk
EXTERNAL INTERFACE	
Network Interface	1; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial Interface	1; standard RS-485 serial interface, half-duplex
USB Port	2 x USB 2.0
GENERAL	
Power Supply	12V DC
Consumption (w/o hard disks)	≤ 30W
Working Temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working Humidity	10%~90%
Chassis	380mm 1U chassis
Dimensions (W x D x H)	380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)

SMART PHONE COMPATIBLE **Guarding Expert**

HDD INSTALLATION AVAILABLE UPON REQUEST
IR REMOTE & MOUSE INCLUDED

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.