16CH TR SERIES















FEATURES

- 16 CH HD TVI video input, 1080P / 720P / WD1 / D1 recording
- 16 CH DVR supports 4 / 8 CH IPC 3MP/1080P/960P/720P/WD1/
- Adopt standard H.264 high profile compression format to get highquality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback: 8 CH simultaneously playback
- Search: time / calendar, events (motion)
- Express and flexible backup via USB, network
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE Network protocol, IE browse and CMS supported
- Remote control via IE or CMS: preview, playback, backup, PTZ and configuration
- Dual stream technology to encode recording stream and network stream respectively. User can adjust network stream to fit bandwidth without changing recording quality
- Multi-user online simultaneously
- Authorization management, log review and device status review
- HDMI 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 128 presets and 8 cruises
- Powerful smart phone surveillance supporting iPhone, Andriod
- Support NAT function, support QR code scanning by mobile phone
- Complete SDK software available, easy to integrate with other applications



*Accessories

	TVST TR2716	
SYSTEM		
Compression	Standard H.264 High Profile	
CPU	Cortex A9	
OS	Embedded Linux	
VIDEO		
Input	BNC x 16	
mpac	Support 1080P@25 / 30fps, 720P@25 / 30 / 50 / 60fps, 960H, D1	
IP Input/Access Bandwidth	IPC x 8 / 24Mbps	
Output	VGA x 1 : 1920 x 1080 , HDMI x 1 : 1920 x 1080	
	AUDIO	
Input / Output	RCA x 1	
2-way audio	Take up channel one audio input	
	RECORD	
Resolution	1080P: 1920 x 1080, 720P: 1280 x 720, WD1, D1	
Frame Rate	720P: 400 fps (PAL) 480 fps (NTSC)	
	1080P: 200 fps (PAL) 240 fps (NTSC)	
Bit Rate	1 M ~ 4 Mbps	
Encode	VBR/CBR	
Quality	6 Level	
Mode	Manual, Timer, Motion	
File Manager	Lock, Unlock, Reserving Time	
IP INPUT		
Resolution	3MP/1080P/960P/720P/WD1/D1	
Frame Rate	3MP: 100 FPS (PAL) 120 FPS (NTSC),	
	1080P/960P/720P: 200 FPS (PAL) 240 FPS (NTSC)	
PLAYBACK		
Playback	8 CH	
Search	Time / calendar search, event (motion)	
Smart Search	Highlighted date and time to display the channel record	
Function	Play, Pause, FF, FB, Digital zoom	
ALARM		
Mode	Motion, Video Loss	
Input / Output	NO	
Triggering	Record, PTZ move, e-mail, etc	
	NETWORK	
Interface	RJ45 10M/100M/1000M adaptive ethernet network port x 1	
Protocal	TCP / IP, UDP, DHCP, DNS, PPPOE, DDNS	
Others	10 users online, dual stream	
CELLPHONE		
OS	iPhone, Andriod	
Function	Multi-screen surveillance, record, snapshot, PTZ control, save the device list	
I/O		
HDD	SATA x 2	
RS485	RS485 x 1, one for PTZ, another for keyboard	
USB	USB 2.0 x 2, one for mouse, another for USB backup device	
Remote Controller	Optional	
OTHERS DO 40V		
Power Supply	DC 12V	
Consumption	< 20W (without HDD)	
Dimensions	430 mm x 300 mm x 55 mm (W x D x H)	
Work Environment	-10 ~ 50 °C , 10% ~ 90% Humidity	