Anti-IR Reflection | EX-SDI 4K(8.3MP) Indoor IR Dome Camera with Vari-Focal Lens, 10 COB IR, 12VDC

1/1.7 inch SONY CMOS (IMX-226) • 30FPS • 0 Lux at IR On (IR LED 10 pcs) • DNR (Digital Noise Reduction) • WDR (Wide Dynamic Range) • Day & Night • Easy Installation • ICR V/F lens, DC Auto IRIS V/F Lens, DC Auto IRIS & TDN V/F Lens • Focal Length : 3.6~10mm

SPECIFICATIONS

Resolution	2160 (UHD) 1080P (HD-SDI)
Sensor	1/1.7 inch SONY CMOS (IMX-226)
Effective Pixels	4074(H) × 3046(V) = 12.4M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	UHD / HDMI 1.4 / SMPTE274M (HD-SDI)
Min.Illumination	0 Lux at IR On
White Balance	AUTO / AUTO EXT / PRESET / MANUAL

Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
Brightness	ADJUSTABLE (0 ~ 20 STEP)
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / MOTION	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating (14°F ~ 122°F(−10°C ~ 50°C) / 30% ~ 80% RH) / Storage (−4°F ~ 140°F(−20°C ~ 60°C) / 20% ~ 90% RH)
Power	DC12V
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : UHD 150M)