

EX-SDI 4MP Outdoor IR Vandal-Resistant Dome Camera with Vari-focal Lens, 2 COB IR, DC 12V



1/2.7" 4Mega Pixel Sensor, TVI 4MP 4IN1 2 Array leds • 2.8-12mm Mega Pixel Lens • Indoor/Outdoor IR Vandal • IR Cut Filter • 2white array leds, 30m-35m IR Distance • Support UTC function, OSD cable, 960H CVBS output. 4IN1, 2D DNR

SPECIFICATIONS

Image Sensor	1/2.7" 4Mega Pixel Sensor
Effective Pixels	4.0 Mega Pixels
Built-in Lens	2.8 ~ 12mm Mega Pixel Lens
Signal System	PAL/NTSC
Horizontal Resolution	PAL:2560 × 1440P 25F/S NTSC:2560 × 1440P 30F/S
Sync. System	Internal Sync.
Sensor Area	38mm × 38mm

EX-SDI 4MP Outdoor IR Vandal-Resistant Dome Camera with Vari-focal Lens, 2 COB IR, DC 12V

Video Output	TVI & CVI & AHD & CVBS Output
S/N Ratio	More than 50dB (AGC OFF)
OSD Menu	Support
White Balance	Auto Tracking White Balance
Shutter Speed	1/25 ~ 50,000Sec.
LEDs	2 COB IRs
Working Temperature	14°F ~ 122°F(-10°C ~ 50°C)
Storage Temperature	-4°F ~ 140°F(-20°C ~ 60°C)
Power Requirement	DC12V, Max Power consumption Less Than 3W (When the infrared lamps turn on)