

804 | 4K (8MP) EX-SDI Brick Camera, 3.6~10mm Vari-focal Lens Included, DC 12V or AC 24V



FEATURES

- 1/1.7 inch SONY CMOS (IMX-226)
- 2160P (UHD), 1080P (HD-SDI)
- Extended Serial Digital Interface
- 1 Lux at F1.2 / 0.1 Lux (B/W)
- OSD Controlled
- Easy Installation
- DNR (Digital Noise Reduction)
- Day & Night
- Vari-focal 3.6 ~ 10mm
- 12VDC or 24VAC Dual Power
- Made in Korea

804 | 4K (8MP) EX-SDI Brick Camera, 3.6~10mm Vari-focal Lens Included, DC 12V or AC 24V

SPECIFICATIONS

Resolution	2160P (UHD), 1080P, HD-SDI
Sensor	1/1.7 inch SONY CMOS (IMX-226)
Total Pixels	4152(H) x 2174(V) = 9.03M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	UHD / SMPTE292M (HD-SDI)
Min.Illumination	1 Lux at F1.2 / 0.1 Lux (B/W)
White Balance	AUTO / AUTO EXT / PRESET / MANUAL
Shutter	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
Brightness	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF / x2 / x4 / x8 / x16 / x32
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485 (PELCO-D)
Operating Temperature / Humidity	-10°C ~ +50°C / 30% ~ 80% RH
Storage Temperature / Humidity	-20°C ~ +60°C / 20% ~ 90% RH
Power	12VDC or 24VAC Dual Power
Signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI (200M) / UHD (150M))