

Anti-IR Reflection | 4K EX-SDI/HD-SDI STORM® IR IP68 Vandal-Resistant Dome Camera with Vari-Focal Lens, 10 COB IR, L-Size, DC 12V



1/1.7 inch SONY CMOS (IMX-226) • 0 Lux at IR On (IR LED 10 pcs) / Upgraded Waterproof Housing (IP 68 rating) • DNR (Digital Noise Reduction) / WDR (Wide Dynamic Range) • Day & Night (ICR Option) / Easy Installation • ICR V/F lens, DC Auto IRIS V/F Lens, DC Auto IRIS & TDN V/F Lens • Focal Length : 3.6~10mm

What is EX-SDI?

Union of great advantages from all existing technologies

HD-SDI

- Digital lossless quality
- Strong resistance to interference

HD-TVI • CVI • AHD


- Long transmission distance
- Able to use video baluns

EX-SDI
THE NEXT GENERATION HD-TECHNOLOGY

Anti-IR Reflection | 4K EX-SDI/HD-SDI STORM® IR IP68 Vandal-Resistant Dome Camera with Vari-Focal Lens, 10 COB IR, L-Size, DC 12V

The Secrets

EX-SDI utilize low frequency signal combine with the new VLC (Visually Lossless CODEC) technology, able to push up 99% identical image quality at more than twice the transmission distance.



Ready for 4K

EX-SDI is built in mind of adopting 4K resolution to security. Thanks to the EX-SDI VLC feature, because of that it is possible to transmit 4K in realtime FPS over coaxial cable.


Backward Compatibility

EX-SDI Magic series will work with any HD-SDI cameras. Just like the Magic series once were compatible with their predecessors' technologies

Video Balun compatible

UTP cable is another option to transmit EX-SDI video signal in order to reduce cable cost. Specialized video balun for EX-SDI is required. (sold separately)

Anti-IR Reflection | 4K EX-SDI/HD-SDI STORM® IR IP68 Vandal-Resistant Dome Camera with Vari-Focal Lens, 10 COB IR, L-Size, DC 12V



SPECIFICATIONS

| | |
|--------------------------|---|
| Resolution | 2160 (UHD) 1080P (HD-SDI) |
| Sensor | 1/1.7 inch SONY CMOS (IMX-226) |
| Effective Pixels | 4074(H) × 3046(V) = 12.4M |
| Scanning System | PROGRESSIVE |
| S/N (Y signal) | More than 52 dB (AGC Off) |
| Video Output | UHD / HDMI 1.4 / SMPTE274M (HD-SDI) |
| Min.Illumination | 0 Lux at IR On |
| White Balance | AUTO / AUTO EXT / PRESET / MANUAL |
| Electronic shutter speed | AUTO / MANUAL (1/30sec ~ 1/60,000sec) |
| Brightness | ADJUSTABLE (0 ~ 20 STEP) |
| DNR | OFF / LOW / MIDDLE / HIGH |
| BACKLIGHT | OFF / WDR / BLC / HLC |
| Day & Night | AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN |
| PRIVACY / MOTION | OFF / ON |
| Language | ENG, CHN, CHN(S), JPN, KOR |
| Sharpness | ADJUSTABLE (0 ~ 10 STEP) |

Anti-IR Reflection | 4K EX-SDI/HD-SDI STORM® IR IP68 Vandal-Resistant Dome Camera with Vari-Focal Lens, 10 COB IR, L-Size, DC 12V

| | |
|----------------------|---|
| COMM. | RS-485(PELCO-D) |
| Temperature/Humidity | Operating (14°F ~ 122°F(-10°C ~ 50°C) / 30% ~ 80% RH) / Storage (-4°F ~ 140°F(-20°C ~ 60°C) / 20% ~ 90% RH) |
| Power | DC12V |
| signal Transmission | The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : UHD 150M) |