



MAGIC Plus

SERIES

FULL HD OVER COAX USE YOUR EXISTING COAX CABLE

HDSDI 2nd Generation



PLUG BOTH **ANALOG & HD-SDI** CAMERAS IN ONE DVR

Magically Detects HD-SDI & Analog Cameras



The First DVR supports

1080p
REAL-TIME RECORDING

MAGIC Plus

SERIES

IT JUST WORKS!

Magic technology bridges the gap between analog security and the next generation high definition digital security.

WHAT IS MAGIC TECHNOLOGY?

Magic Technology is designed to adopt various video signal types in a single Digital Video Recorder. In other words, any past generation analog CCTV cameras you own, as well as HD-SDI - high definition digital CCTV- cameras will work seamlessly with the Magic DVR.



SMART PHONE COMPATIBLE

MR.Patrol



REAR PANEL



XVST MAGIC-PLUS04

- Real-Time Live Display and Recording
- H.264[®] High Compression Codec
- High Speed Network Video Transmission
- Advanced PTZ Control
- Programmable Spot Out
- Crystal Clear 1080p Blu-Ray Quality Live Video
- Smart Phone Support

HDD INSTALLATION AVAILABLE UPON REQUEST
IR REMOTE & MOUSE INCLUDED

MADE IN KOREA

1. Cellular data service required. Software may not compatible due to OS version requirements

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.



FULL HD OVER COAX USE YOUR EXISTING COAX CABLE


HDSDI[™] 2nd Generation



Upgrade just can't get any easier than this, just unplug all cameras from the old DVR and plug them back into the new Magic DVR, it will just work. Absolutely no training or knowledge is necessary.

The best feature about the DVR is that both analog and HD-SDI cameras work in a single DVR. FULL HD security is not a luxury option any more, it is a must for today's security.

HOW MAGIC DVR WORKS



FREE DDNS SERVICE

HDMI OUTPUT

- Full Gui With Alpha Blending
- Individual Setting Of Resolution, Frame Rates & Picture Quality
- Instant Replay
- Digital Zoom (Live & Playback) / Mouse Control
- Weekly Scheduler With Holiday By 10 Minutes Setting
- Covert, Disable And Private Function Of Cameras
- Motion Detection With 352 Area Settings
- Relay Alarm Output
- Ptz Control By Rs-485
- Daylight Saving Time And Network Time Setting
- Multi User Authority Up To 8 Users
- De-Interlacer Upon Live And Playback
- 22 Languages With Full Graphic
- Individual Network Port Setting
- Auto Deletion
- Import And Export The Configuration
- Mirroring
- Pos Interface
- Dual Codec Engine For Independent Video Transmission
- Interactive Setup Via Network

ACCESSORIES



XVST MAGIC-PLUS04		
Video	Camera Input	4 BNC
	Individual HD/Analog Selectable	Quattro-brid
	Available Source	IP camera/HD-SDI 720p25,30,50,60/HD-SDI 1080p25,30,50,60/1080i50,60/Composite/960H/Mixed/Another DVR
	IP Camera	Spec Number Restriction
Output		1 HDMI (Main Display or Programmable HD Spot) 1 VGA (Main Display or Programmable HD Spot) 1 Composite (Programmable SPOT)
Audio Input/Output		4 RCA/1 RCA
Sensor In		4 (NC, NO Selectable)
Alarm Out		1 Relay
Operating System		Embedded Linux OS
Display	Speed	Real Time
	Resolution (Pixel)	1280X1024, 1280X720, 1920X1080
	Split Screen	1,4
Main Recording	CODEC	H.264
	Resolution (Pixel)	720p, 1080p, 960H, 720H, WCIF, CIF Mixed
	Picture Quality	4 steps (Super, High, Medium, Low)
Dual Recording	NTSC Area/PAL Area	120fps@1080p 100fps@1080p
	CODEC	H.264
	Condition	Main Recording is 1080p, 720p
Playback	Resolution (Pixel)	N/A
	Display	1,4
	Search Mode	Calendar, Event, POS, Panorama, Thumbnail
	NTSC Area/PAL Area	60fps@1080p 100fps@1080p
Network	Fast/Slow Speed	Normal, REW & FF [recorded speed x2, x4, x8, x16,x32,x64,x-1/2,x1/4], Frame to frame, Pause
	Network Interface	Gigabit Ethernet X 1
	Speed	15fps@1080p
	Protocol	TCP/IP, HTTP, DHCP
	Application	Windows 7 / 8 (PC Client system& IE)/MAC
Backup	Web Browser	Internet Explorer, Safari, Chrome, Firefox
	Smart Phone APP	Android, iPhone for Live and Search
	Interface	USB 2.0 X 2
Backup Device	External HDD, CD & DVD-RW, Network, Thumb Drive	
The Number of HDD		2 SATA
Other	Power Consumption	60W
	Operating Temperature	5 ~40 °C(41~104F)
	Relative Humidity	Maximum 80% non-condensing
	Dimension	340(W)×250(D)×60(H)

HDD INSTALLATION AVAILABLE UPON REQUEST
IR REMOTE & MOUSE INCLUDED

MADE IN KOREA

1. Cellular data service required. Software may not compatible due to OS version requirements

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.