

## CMHT2322-28F 2 MP 4-in-1 Turret Camera



### Key Features

- 2 MP high performance CMOS
- 2.8 mm fixed lens
- 2D DNR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66

## Specification

<b>Camera</b>	
Imaging Device	1/3" Progressive CMOS
Min. Illumination	0.05lux@F1.2(AGC ON), 0Lux with IR ON
Video Output	BNC
Resolution	2MP 1920(H)×1080(V)
Max. Framerate	AHD/TVI/CVI: P/@25fps N/@30fps CVBS: 960H
Focal Length (Zoom Ratio)	2.8MM
Max. Aperture Ratio	F2.0
Angular Field of View	H:91.84° / V:50.04° / D:107.73°
Min. Object Distance	0.6m
Lens Type	Fixed lens
<b>Menu</b>	
IR Range	Up to 66ft(20m)
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Video Transmission Distance	MAX 300m (Cable: 5C 2V)
<b>General</b>	
Operating Temperature / Humidity	-30°C ~ 50°C (-22 °F to 122 °F), Humidity: 90% or less (non-condensation)
Ingress Protection	IP66
Input Voltage/Current	12V DC
Power Consumption	IR ON : 3.5W, IR OFF : 0.5W
Color / Material	Metal
Dimension	Φ100mm×90mm (Φ3.94"×3.54")
Weight	appr. 370g (0.82 lb.)

## Dimension

