SUPERDOME® 650TVL Indoor Dome Camera w/ Auto-Iris VF Lens



1/3 INCH SONY DS CCD • High Resolution (650 TVL) • High Sensitivity • 0.3Lux at F1.2 (Color) • 0.005Lux (Sense up x256) • WDR (Wide Dynamic Range) Function • OSD Controlled • Ture Day & Night (ICR) • 3DDNR • HLM • Motion (240 Zone) • Privacy • Easy Installation • 3Axis • DC Auto IRIS V/F Lens 2.8~12mm • DC Auto IRIS & TDN V/F Lens 2.8~12mm

SPECIFICATIONS

MODEL	NTSC / PAL
Sensor	1/3 INCH SONY DS CCD
Total Pixels	NTSC: 811(H) × 508(V) 410K pixels PAL: 795(H) × 595(V) 470K pixels
Effective Pixels	NTSC: 768(H) × 494(V) 380K pixels PAL: 752(H) × 582(V) 440K pixels
Scanning System	2:1 Interlace
S/N (Y signal)	More than 52 dB (AGC Off)
Frequency	NTSC: Horizontal: 15.734KHz / Vertical: 59.94Hz PAL: Horizontal: 15.625KHz / Vertical: 50.00Hz
Video Output	CVBS: 1.0Vp-p / 75ohm
Min.Illumination	0.3Lux at F1.2 (Color) / 0.005Lux (Sense up × 256)
White Balance	ATW / AWC / PUSH/ MANUAL Adjustable
Electronic shutter speed	NTSC: AUTO / MANUAL (1/60sec ~ 1/100,000sec) PAL: AUTO / MANUAL (1/50sec ~ 1/100,000sec)
WDR (Wide Dynamic Range)	AUTO, OFF Selectable
O.S.D	Built-in
Backlight Compensation	BLC (LOW, MIDDLE, HIGH, OFF Selectable) / HLM (Adjustable)
AGC (Auto Gain Control)	LOW, MIDDLE, HIGH, OFF Selectable
3DDNR (3D Digital Noise Reduction)	LOW, MIDDLE, HIGH, OFF
Day & Night	AUTO (Day <--> Night time Change) , CDS , COLOR , B/W
PRIVACY	OFF / ON (6 Zone)
Motion Detection	OFF / ON (240 Zone)
Image Conversion	FREEZE / V-FLIP / H-FLIP / ROTATE / NEGA : All ON /OFF Adjustable
DIS(Digital Image Stabilizer)	ON / Off
LSC (Lens Shading Compensation)	ON / Off
Digital Zoom	ON (× 1 ~ 10) / Off
SHARPNESS	ADJUSTABLE
Operating Temperature/ Humidity	14°F ~ 122°F(−10°C ~ 50°C) / 30% ~ 80% RH
Storage Temperature/ Humidity	−4°F ~ 140°F(−20°C ~ 60°C)/ 20% ~ 90% RH
Power	DC12V [AC24V / DC12V DualPower (option)]