LTD2424MD D1/ 24 Channel High Performance DVR (MD Series)

Features

- Real-Time High Resolution Recording
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via CMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 2 Year Warranty & Free Life-Time Technical Support

H.264 COMPRESSION | DUAL STREAM | CMS | WATERMARK | 2-Way AUDIO | FREE DDNS | FREE LOGO | 2 year warranty

Specifications

System	Compression Format	H.264
	OS	Embedded Linux
Video	Input	24CH, BNC (1.0Vp-p, 75Ω)
	VGA Output	1*VGA:1280x1024, 800x600, 1024x768
	BNC	1*BNC Mainout
	Loop Output	1*Loopout
	Spot Output	1*Spot
	HDMI	Compatible with HDMI 1920x1080 output, progressive scan, 60Hz frame rate.
Audio	Audio Input	16CH
	Audio Output	1CH
	Bidirectional Talk	YES
Recording	Real Time Recording	4CH D1, 20CH CIF real time
	D1	270(NTSC)/225(PAL)fps
	CIF	720(NTSC)/600(PAL)fps
	Recording Mode	Schedule, Manual,Motion, Sensor
Playback	Playback Channel	16CH
	Search Mode	Time, Event, File Management, Image(snapshot)
Backup	USB Disk	-
	DVD Burner	Optional
	Backup Format	DAT or AVI
Dual Steam	Master Stream	30 fps@D1
	Network Stream	1-30 fps@CIF
Remote Application	Browser	IE (windows XP/vista/7), Safari(Mac OS)
	CMS	YES
	Mobile Phone OS	SuperCam/pro/HD for iPhone(iPad/iPad2)/ Blackberry/Android
	User Access	10 users online with professional authority management
Alarm	Alarm Input	16CH
	Alarm Output	4CH
Storage	HDD (Each max. size 2 TB)	4
	e-SATA	1
	Max HDD after Deploying DVD Writable Driver	3
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCOP,PELCOD,LILIN,MINKING,NEON, STAR,VIDO,DSCP, VISCA, SAMSUNG, RM110,HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	1,000 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
Others	Remote Control	1
	Power Supply	100VAC ~ 240VAC
	Operating Temperature	0°C ~50°C
	Humidity	10% ~ 90% Humidity
	Dimension	

Front/Back View