EYEMAX (Made in Korea) Indoor IR Network Dome Camera P4642V | 4.2MP, Anti-IR Reflection, 6 COB IR, Vari-focal Lens, 12VDC / PoE



1/3" CMOS image sensor • High Definition IP Camera Module • IR LED 06 pcs • DNR (Digital Noise Reduction) • WDR (Wide Dynamic Range) • Day/Night switch • Easy Installation • ICR V/F lens • DC Auto IRIS V/F Lens • DC Auto IRIS & TDN V/F Lens • (Focal Length : 2.8~12mm)

Mount Accessories

Plastic Wall Mount Bracket	**DO WB201**

SPECIFICATIONS

Resolution	4MP High Definition IP Camera Module
Sensor	1/3" CMOS image sensor
Image Output	Main stream：2560*1440@20fps;Auxiliary stream and third stream optional
Video Bite rate	32Kbps~8MKbps
Electronic shutter	Auto：1/25 to 1/10000；
Day/Night switch	Auto/color/B&W：Built-in IR_CUT；
DNR	2D, 3D
WDR	Support DWDR
Video Adjustment	Sharpness, Brightness, Saturation, Contrast Adjustable
Lan	10/100BaseT Ethernet auto sensing
Motion detection	Multiple detection zones, variable sensitivity levels
Screenshots	JPEG：capture resolution is the max coding resolution
Security	Password protection and water marker
Mobile APP	VSSMOBILE for both iPhone and Android system phone
Interface protocol	ONVIF/CGI
Power Supply	DC12V/POE(-P)
Power Consumption	<1.7W