960p IP CAMERA

- IR Bullet Type
- 1/3" Aptina CMOS
- 1.3MP (960p)
- 3.6mm Fixed Lens
- 30 IR LEDs
- MJPEG / UPNP
- DC 12V
- Mechanical IR-Cut Filter
- Power over Ethernet (PoE)

H.264 ONVIF IR-Cut Filter Removal ICR True Day & Night

FEATURES

- 1/3" Line Scanning Digital and Advanced DSP Technology
- Picture Resolution 960p Color CMOS, 1.3 Mega Pixel, 1280×960
- Optimized H.264 Main Profile compression algorithm, high compression ratio and high quality image; convenient to realize a transmission of HD images on a narrow band, thus it can save the storage space; support triple bit streams
- The most advanced network delivery server technology, Easily achieve more user access, Multi-stage user password rights management
- Built in Web Server, through the IE browser easy to realize the remote control Settings prison see operation
- Support facilities remote security upgrade function
- Support DDNS, PPPoE and UPnP, Support LAN, WAN transport.
- Technology of self adaptability to network that it may adjust its video flame rate automatically according to the bandwidth of network
- Functions of alarm in video missing, mobile detection, probe, or etc. (Available to set the regions and sensitivity)
- Support Mobile Detection / Image Shielding / Image Snapshot
- Functions of auto recovery in abnormality and auto reconnection in network breakdown

NIR B1332F		
Camera	Pixel	1.3 Mega Pixel, 1280"960
	Sensor	1/3" 1.3M Aptina CMOS
	Lens	3.6mm
	Electronic Shutter	1/25s-1/30,000s
	Low Lux	Color : 0.1Lux@F1.6 B/W:0.01Lux@F1.6
	ICR	Support
	Video Parameter	Saturation, brightness, contrast ratio and color tone can be adjusted by customer end or IE explorer
IR	IR Properties	Dual Filter Day / Night: Automatic Switch, Linkage Switch
	IR Light	30pcs 5Ø IR LEDS
Audio-Video Coding Parameters	Compression	H.264 Main Profile@Level 3.0 / MJPEG optional
	Video Bit Rate	0.1M-6Mbps, Customized
	Bit Stream Type	Video Stream
	Audio Compress	N/A
	Audio Bit Rate	N/A
	Triple Bit Streams	Support
Image	Video Resolution	1280×960
	Video Flame Rate	PAL: 1-25 frames/second, NTSC: 1-30 frames/second
Function	PTZ	N/A
	Heartbeat Mechanism	Support
	IP Auto Pop-Out	IP auto pop-out at customer end
	Password Protection	Multi-level protection on password
	Intellectual Alarm	Mobile Detection, Video Shielding, Video Loss, Network Breakdown, Abnormality in Storage
	Basic Functions	One-Key Reset, Password Protection, Watermark Technology
Interface	Audio Input	N/A
	Video Output	N/A
	Network Port	1 pcs, RJ45 10M/100Mbps Self-Adaptable Ethernet Port
	Serial Port	N/A
	Alarm Input	N/A
	Alarm Output	N/A
Wireless Network	WIFI	N/A
	Wireless Encryption Protocol	N/A
	Cell Phone Monitor	Support
	3G Network	N/A
others	POE	802.3af
	Power Supply	DC12V/1.5A
	Power Consumption	<6W
	Working Temp	-10°C ~ +55°C / 14°F ~ 131°F
	Working Humidity	10 ~ 85%
	Dimension	L172mm×W74mm×H64mm

Specifications may change without a prior notice. All the images on the page are for illustrative purpose only. They may not representing actual products. All the rights for the registered trademarks are reserved for their respectable owners. Not responsible for any typographical errors.