IP Power MC532V | 5MP Network IP66 Outdoor IR Eyeball Camera, H.265, 2.8 ~ 12mm Motorized VF Lens, up to 100ft, DC 12V / PoE





FEATURES

- 5MP (2592 × 1944) H.265 coding
- Max. resolution: 2592 × 1944
- ICR auto switch, true day / night
- 20 ~ 30m (100ft) IR night view distance
- Motorized lens
- 3D DNR, digital WDR, ROI coding
- PoE power supply
- Support smart phone, iPad, remote monitoring
- IP66 ingress protection
- Support three streams

SPECIFICATIONS

Camera	
Image Sensor	1 / 2.7" CMOS
Image Size	2592 × 1944
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Iris Type	Fixed iris
Min. Illumination	0.013 lux @F1.2,AGC ON; 0 lux with IR
Lens	2.8 ~ 12mm
Lens Mount	∅14
Day & Night	ICR
Wide Dynamic Range	Digital WDR
Digital NR	2D / 3D DNR
Angle Adjustment	Any angle
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	5MP (2592×1944), 4MP (2592×1520), 2K (2560×1440), 3MP (2304×1296), 1080P (1920×1080), 720P (1280×720), D1, CIF, 480×240
Main Stream	60Hz : 5MP (1 ~ 20fps) / 4MP (1~30fps) / 2K(1 ~ 30fps) / 3MP(1 ~ 30fps) / 1080P(1 ~ 30fps) / 720P(1 ~ 30fps) 50Hz : 5MP (1 ~ 20fps) / 4MP (1~30fps) / 2K (1 ~ 25fps) / 3MP (1 ~25fps) / 1080P (1 ~ 25fps) / 720P (1 ~ 25fps)
Bit Rate	128 Kbps ~ 10 Mbps
Bit Rate Type	VBR / CBR
Quality	Five levels under VBR; Freely adjustable under CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, Antiflicker, etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Interfaces	
Network	RJ45
Functions	

Remote Monitoring	Web browsing, CMS remote control
Online Connection	Support simultaneous monitoring for up to 6 users; Support multi-stream real time transmission
Network Protocol	IPv4, IPv6, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, QoS
Interface Protocol	ONVIF
Storage	Network remote storage
Smart Alarm	Motion alarm
PoE	Yes
IR Distance	20 ~ 30m (100ft)
Ingress Protection	IP66
Others	
Power Supply	DC12V /PoE power supply
Power Consumption	< 9.5W
Operating Environment	− 30°C ~ 60°C,humidity 95% or less (non-condensing)
Dimensions (mm)	∅ 110 × 130
Weight (net)	675g