Eyemax IR-E4004 | 4MP Starlight Outdoor PTZ Camera, 4× Optical Zoom, SMD Plus, 50ft IR Range, True WDR, WizSense, AI Series, IVS, 12VDC/PoE



1/2.8" 4Megapixel STARVIS CMOS • Starlight technology • Max. 25/30fps@4MP • 4× optical zoom • Face Detection, People Counting, Perimeter Protection • IR distance up to 15m • SMD Plus • PoE • IP66, IK08

WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on our advanced technologies, Wiz-Sense provides intelligent, simple and inclusive products and solutions.

System Overview

WizSense PTZ camera adopts advanced CNN deep learning algorithms to support perimeter protection with high accuracy. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

People Counting

People Counting function uses advanced image processing technology to capture depth information from within images. The camera pairs this information with deep learning algorithms to analyze and detect human bodies and track target objects in real time. The camera provides statistics for separate individuals' entrance and exit with up to 95% counting accuracy.

Starlight Technology

For challenging low-light applications, Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Environmental

Cameras operate in extreme temperature environments, rated for use in temperatures from -30°C to +60°C (−22°F to +140°F) with 95% humidity. Subjected to rigorous dust and water immersion tests and certified to the IP66 Ingress Protection rating makes it suitable for demanding outdoor applications.

Protection

The camera allows for ±15% input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 6KV lightning rating provides effective protection for both the camera and its structure against lightning.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR optimizes both the bright and dark areas of a scene at the same time to provide usable video.

H.265+

H.265+ is the optimized implementation of the H.265 CODEC that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

FEATURES

- 1/2.8" 4Megapixel STARVIS™ CMOS
- Starlight technology
- Max. 25/30 fps@4MP
- 4&tiems; optical zoom
- Face Detection, People Counting, Perimeter Protection
- IR distance up to 50 ft (15 m)
- SMD Plus
- PoE
- IP66, IK08

SPECIFICATIONS

Camera	
Image Sensor	1/2.8" STARVIS™ CMOS
Pixel	4MP
Max. Resolution	2560 (H) × 1440 (V)
ROM	4GB

RAM	1GB
Electronic Shutter Speed	1 / 1 s ~ 1 / 30,000 s
Scanning System	Progressive
Min. Illumination	Color: 0.005Lux@F1.8 B/W: 0.0005Lux@F1.8 0Lux (IR light on)
Illumination Distance	15 m (49.21 ft)
Illuminator On/Off Control	Zoom Prio / Manual / Smart IR
Illuminator Number	3
Lens	
Focal Length	2.8 mm–12 mm
Max. Aperture	F1.8–F2.7
Field of View	H: 31.6°–96.9° V: 17.8°–51.4° D: 36.4°–116.2°
Optical Zoom	4x
Focus Control	Auto / Semi-Auto / Manual
Close Focus Distance	0.2 m–0.5 m (0.66 ft–1.64 ft)
Iris Control	Auto
DORI Distance	Detect: 147.0 m (482.28 ft) / Observe: 58.8 m (192.91 ft) / Recognize: 29.4 m (96.46 ft) / Identify: 14.7 m (48.23 ft)
PTZ	
Pan/Tilt Range	Pan: 0°–355° Tilt: 5°–90°
Manual Control Speed	Pan: 0.1°/s–70°/s Tilt: 0.1°/s–30°/s
Preset Speed	Pan: 80°/s Tilt: 40°/s
Presets	300
Tour	8 (up to 32 presets per tour)
Speed Adjustment	Support
Power-off Memory	Support
Idle Motion	Preset/Tour
General Intelligence	

Event Trigger	Motion detection, Video tampering, Scene changing, Network disconnection, IP address conflict, Illegal Access, Storage anomaly
IVS	Object Abandoned/Missing
Artificial Intelligence	
People Counting	Count people entering and exiting the area (crossing people counting); count people staying in the area (in- area people counting); display and export reports by day, week and month.
Perimeter Protection	Tripwire and intrusion. Support alarm triggering by target types (human and vehicle). Support filtering false alarms caused by animals, rustling leaves, bright lights, etc.
SMD Plus	Support
Face Detection	Support
Video	
Compression	H.265; H.264BaselineProfile; H.264MainProfile;H.264HighProfile; MJPEG (Sub Stream); H.265+; H.264+
Streaming Capability	3 streams
Resolution	4M (2560 × 1440); 3M (2048 × 1536); 1080P (1920 × 1080); 1.3M (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480); CIF (352 × 288/352 × 240)
Frame Rate	Main stream: 4M/3M (1–25/30fps), 1080P/1.3M/720P (1–25/30fps) Sub stream 1: D1/CIF (1–25/30fps) Sub stream 2: 720P (1–25/30fps), D1/CIF (1–25/30fps)
Bit Rate Control	Variable Bit Rate/Constant Bit Rate
Bit Rate	H.264/H.265/MJPEG: 3 kbps–20480 kbps
Day/Night	Auto (ICR)/Color/B/W
BLC	Support
WDR	120 dB
HLC	Support
White Balance	Auto/Indoor/Outdoor/Track/Manual/Sodium lamp/ Natural light/Street lamp
Gain Control	Auto/Manual
Noise Reduction	2D/3D
Motion Detection	Support
Region of Interest (RoI)	Support
Electronic Image Stabilization	Support

Electronic Defog	Support
Digital Zoom	16x
Flip	0°/180°
Privacy Masking	Up to 24 areas, and up to 8 areas in the same view
Audio	
Compression	G.711a; G.711Mu; G.726; AAC; MPEG2-Layer2; G.722.1; G.729; G.723
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4; IPv6; HTTP; HTTPS; 802.1x; Qos; FTP; SMTP; UPnP; SNMPv1/v2c/v3(MIB-2); DNS; DDNS; NTP; RTSP; RTP; TCP; UDP; IGMP; ICMP; DHCP; PPPoE; ARP; RTCP
Interoperability	ONVIF Profile S&G&T; CGI
Streaming Method	Unicast/Multicast
User/Host	20
Storage	FTP; Micro SD card (256G); P2P
Browser	IE; Chrome; Firefox; Safari (no version restriction)
Management Software	SmartPSS / DSS
Mobile Phone	iOS/Android
Certification	
Certifications	CE: EN55032/EN55024/EN50130 ~ 4 FCC: Part15 subpartB, ANSI C63.4 ~ 2014 UL62368 ~ 1+CAN/CSA C22.2,No. 62368 ~ 1
Port	
Audio Input	1(Line in; bare wire or built in Mic)
Audio Output	1
Power	
Power Supply	DC12V/1.5A±15% PoE (802.3af)
Power Consumption	3W / 8.5W (IR on)
Environment	
Operating Temperature	−30°C to +60°C (−22°F to 140°F)
Operating Humidity	≤95%
Protection	IK08; IP66; TVS 6000V lightning proof; surge protection

Structure	
Dimensions	∅128.0 mm × 65.4 mm (5.04" × 2.57")
Net Weight	0.485 kg (1.06 lb)
Gross Weight	0.7 kg (1.54 lb)