8CH H.265 Network Video Recorder (NVR) with 8 PoE, 12MP, 80Mbps Input, 2xSATA, HDMI(4K)





8 Channel & 8 POE Network Video Recorder · Up to 8Ch. IP cameras input · 80 Mbps Bit rate Input Max and 160 Mbps Bit rate Output Max · Third-party network cameras supported · Up to 12MP resolution recording · Independent VGA and HDMI output · VGA output up to 1080p@60Hz, HDMI output up to 4K@30Hz · 2 SATA HDD interface up to 8TB each

SPECIFICATIONS

Video Compression	H.264 / H.264+ / H.265 / MPEG4
IP Video Input	8 Ch. (80 Mbps Max input)
Video Output	1 HDMI, 1 VGA
Audio Input/Output	1/1
Two-way Audio	1/1
Real-time recording resolution	Up to 12 Megapixels

HDMI Output Resolution	4K, 3840×2160@30Hz, – 2K 2560×1440@60Hz, 1920×1080@60Hz, 1600×1200@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
VGA Output Resolution	1920×1080@60Hz, 1280×1024@60Hz, 1280×720@60Hz, 1024×768@60Hz
Synchronous Playback	8-ch, (2-ch @ 4K, or 8-ch @ 1080p)
Network Interface	1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
PoE Network Interfaces/Built-in switch	8 independent 10/100 Mbps PoE network interfaces
Internal SATA	2 SATA interfaces (up to 8TB each)
Alarm I/O	4/1
USB interface	1 x USB2.0 and 1 x USB 3.0
Operation Temperature	-10 °C ~ +55 °C
Chassis	385mm chasis
Dimension	15.2″W x 12.4″D x 2.0″H
Power Supply	100 ~ 240VAC
Power Consumption	Max. 15W
Weight	6.6 lbs (without hard disk)