Eyemax | Network Keyboard Controller for Eyemax High Speed Dome, Standalone DVR and Network Video Server



RS485, RS422, USB, RS232 connection • 3D Joystic control of PTZ Functions • Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions • On-Screen Menu • Connect to SmartPSS via USB

Keyboard to Control

- Eyemax High Speed Dome
- Eyemax Standalone DVR

- Eyemax Network High Speed Dome
- Network Video Server

Connection

- RS485, RS422, USB, RS232 & Network

Functions

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to SmartPSS via USB

SPECIFICATIONS

General	
Keyboard Key panel	Electromechanical
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: DH-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P, etc
Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
Display	LCD, 75.2mm × 33.85mm
General	
Power Supply	Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA
Power Consumption	5W
Working Temperature	−10°C ~ +55°C
Working Humidity	10% ~ 90%
Atmosphere Pressure	86kpa ~ 106kpa

Dimension	330 × 160(140)mm × 37.5(21)mm (W×D×H) (height: 100mm including joystick)
Weight	2.5kg (Including package)