STORM® 620TVL Dome Camera w/ Auto-Iris VF Lens

1/3 INCH SONY SUPER HAD CCD II • High Resolution (620 TVL) • High Sensitivity Upgraded Waterproof Housing (IP68 rating) 0.1Lux at F1.2 (Color) • 0.01Lux (B/W) • OSD Controlled • Day & Night • 2DNR • HLC • Motion • Privacy • Easy Installation • 3Axis 3.6mm Fixed Lens

SPECIFICATIONS

Model	NTSC
Sensor	1/3 INCH SONY SUPER HAD CCD II
Resolution	620 TV Line
Total Pixels	811(H) × 508(V) 410K Pixels
Effective Pixels	768(H) × 494(V) 380K Pixels
Scanning System	2:1 Interface
S/N (Y signal)	More than 50 dB (AGC Off)
Frequency	Horizontal: 15.734KHz / Vertical: 59.94Hz
Video Out	CVBS: 1.0Vp-p / 750ohm
Min Illumination	0.1 Lux at F1.2(color) / 0.0001Lux (sense up × 256)
White Balance	AWT1 / AWT2 / AWC ->SET/MANUAL Ajustable
Electronic Shutter Speed	AUTO/MANUAL(1/60sec ~ 1/100,000sec)
OSD	Built-in
Backlight Compensation	BLC (LOW/MIDDEL/HIGH/OFF Selectable
2DNR (2D Digital Noise Reduction)	ON/OFF
AGO(Auto Gain Control)	LOW/MIDDLE/HIGH/OFF Selectable
Day & Night	ATUO / COLOR / BW / EXT
Privacy	OFF/ON (8 Zone)
Motion Detection	OFF/ON (Motion size: 28 × 15, 4 area)
Image Conversion	ON/OFF
Sharpness	Adjustable

Operating Temperature/Humidity	−10°C ~ 50°C / 30 ~ 80% RH
Storage Temperature / Humidity	−20°C ~ 60°C / 20 ~ 90% RH
Power	DC12V [AC24V / DC12V DualPower(option)]