STORM® 650TVL Dome Camera w/ Auto-Iris VF Lens

1/3 INCH SONY DS CCD • High Resolution (650 TVL) • High Sensitivity • Upgraded Waterproof Housing (IP68 rating) • 0.3Lux at F1.2 (Color) • 0.005Lux (Sense up x256) • WDR (Wide Dynamic Range) Function • OSD Controlled • Ture Day & Night (ICR) • 3DDNR • HLM • Motion (240 Zone) • Privacy • Easy Installation • 3Axis • DC Auto IRIS V/F Lens 2.8~12mm • DC Auto IRIS & TDN V/F Lens 2.8~12mm

SPECIFICATIONS

MODEL	NTSC
Resolution	650 TV Line
Sensor	1/3 INCH SONY DS CCD
Total Pixels	811(H) × 508(V) 410K pixels
Effective Pixels	768(H) × 494(V) 380K pixels
Scanning System	2:1 Interlace
S/N (Y signal)	More than 52 dB (AGC Off)
Frequency	Horizontal: 15.734KHz / Vertical: 59.94Hz
Video Output	CVBS: 1.0Vp-p / 75ohm
Min.Illumination	0.3Lux at F1.2 (Color) / 0.005Lux (Sense up × 256)
White Balance	ATW / AWC / PUSH/ MANUAL Adjustable
Electronic shutter speed	AUTO / MANUAL (1/60sec ~ 1/100,000sec)
WDR (Wide Dynamic Range)	AUTO, OFF Selectable
O.S.D	Built-in
Backlight Compensation	BLC (LOW, MIDDLE, HIGH, OFF Selectable) / HLM (Adjustable)
AGC (Auto Gain Control)	LOW, MIDDLE, HIGH, OFF Selectable
3DDNR (3D Digital Noise Reduction)	LOW, MIDDLE, HIGH, OFF
Day & Night	AUTO (Day <--> Night time Change) , CDS , COLOR , B/W
PRIVACY	OFF / ON (6 Zone)
Motion Detection	OFF / ON (240 Zone)

Image Conversion	FREEZE / V-FLIP / H-FLIP / ROTATE / NEGA : All ON /OFF Adjustable
DIS(Digital Image Stabilizer)	ON / Off
LSC (Lens Shading Compensation)	ON / Off
Digital Zoom	ON (× 1 ~ 10) / Off
SHARPNESS	ADJUSTABLE
Operating Temperature/ Humidity	14°F ~ 122°F(−10°C ~ 50°C) / 30% ~ 80% RH
Storage Temperature/ Humidity	−4°F ~ 140°F(−20°C ~ 60°C) / 20% ~ 90% RH
Power	DC12V [AC24V / DC12V DualPower (option)]