HD-TVI Indoor Dome Camera / 1080P(2MP) / 2.8~12mm AI-VF MP / DC 12V/AC 24V



1/2.9 INCH SONY CMOS (IMX-222) • RESOLUTION (1080P • 720P • 720P CROP] • TRANSPORT VIDEO INTERFACE • HIGH RESOLUTION • OSD CONTROLLED • SMART IR (IR PRODUCT SPEC) • WDR (WIDE DYNAMIC RANGE] • DAY & NIGHT(ICR OPTION) • DNR (DIGITAL NOISE REDUCTION) • OPTION (RS-485) • EASY INSTALLATION

Mount Accessories

Plastic Wall Mount Bracket	**DO WB201**

SPECIFICATIONS

RESOLUTION	1080P, 720P, 720P CROP
SENSOR	1/2.9 inch SONY CMOS (IMX-222)
TOTAL PIXELS	2000(H) × 1241(V) =. 2,482,000
EFFECTIVE PIXELS	1944(H) × 1092(V) = 2,122,648
SCANNING SYSTEM	PROGRESSIVE
SIN (Y SIGNAL)	More than 52 dB (AGO Off)
VIDEO OUTPUT	TVI / (CVBS: 1.0Vp-p (75ohm) . Option)
MIN.ILLUMINATION	IR PRODUCT : 0 Lux at PR On GENERAL PRODUCT : 1 Lux at F1.2 / 0.1 Lux (BAN)
WHITE BALANCE	AUTO / AUTO EXT /PRESET / MANUAL
SHUTTER	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
BRIGHTNESS	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF/X2 /X3 /X4 /X5/X6 /X7 /X8
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLM
ACE	OFF / LOW / MIDDLE / HIGH
DAY & NIGHT	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN, MDIR (SEARCH Option)
PRIVACY	OFF / ON (16 Zone)
MOTION	OFF / SET
D.ZOOM	0 ~ 127
FLIP	OFF / ON
FREEZE	OFF/ON
LANGUAGE	ENG, CHN, CHN(S), JPN, KOR
SHARPNESS	ADJUSTABLE (0 ~ 10 STEP)
DEFOG	OFF/SET
COMM	RS-485 (PELCO-D)
SMART IR (IR PRODUCT SPEC.)	ADJUSTABLE (0 ~ 20 STEP)
OPERATING TEMPERATURE / HUMIDITY	14°F ~ 122°F(−10°C ~ 60°C) / 30% ~ 80% RH

STORAGE TEMPERATURE / HUMIDITY	−4°F ~ 140°F(−20°C-A-60°C) / 20% ~ 90% RH
POWER	AC24V / DC12V DualPower (option)
SIGNAL TRANSMISSION	The distant difference is occurred according to cable option and other circumstances. (coaxial cable 300M)