HD-TVI Outdoor Dome Camera(IP68) / 1080P(2MP) / 3.6mm MP / DC 12V



1/2.9 inch SONY CMOS (IMX-222) • Resolution (1080P • 720P • 720P CROP) • TVI (Transport Video Interface) • 1 Lux at F1.2 • 0.1 Lux (B/W) • Upgraded Waterproof Housing (IP68rating) • DNR (Digital Noise Reduction) • Day & Night (ICR Option) • Option (RS-485) • Easy Installation • 3Axis • fixed Lens 3.6mm

SPECIFICATIONS

RESOLUTION	1080P, 720P, 720P CROP
SENSOR	1/2.9 inch SONY CMOS (IMX-222)
TOTAL PIXELS	2000(H) × 1241(V) = 2,482,000
EFFECTIVE PIXELS	1944(H) × 1092(V) = 2,122,648
SCANNING SYSTEM	PROGRESSIVE
S/N (Y SIGNAL)	More than 52 dB (AGC Off)
VIDEO OUTPUT	TVI / (CVBS: 1.0Vp-p (75ohm) : Option)
MIN.ILLUMINATION	1 Lux at F1.2 / 0.1 Lux (B/W)
WHITE BALANCE	AUTO / AUTO EXT / PRESET / MANUAL
SHUTTER	AUTO / MANUAL (1/30sec ~ 1/60,000sec)
BRIGHTNESS	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP	OFF / × 2 / × 3 / × 4 / × 5 / × 6 / × 7 / × 8
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLM
ACE	OFF / LOW / MIDDLE / HIGH
DAY & NIGHT	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN, MDIR (SEARCH Option)
PRIVACY	OFF / ON (16 Zone)
MOTION	OFF / SET
D.ZOOM	0 ~ 127
FLIP	OFF / ON
FREEZE	OFF / ON
LANGUAGE	ENG, CHN, CHN(S), JPN, KOR
SHARPNESS	ADJUSTABLE (0 ~ 10 STEP)
DEFOG	OFF / SET
COMM	RS-485 (PELCO-D)
SMART IR (IR PRODUCT SPEC.)	ADJUSTABLE (0 ~ 20 STEP)
OPERATING TEMPERATURE / HUMIDITY	14°F ~ 122°F(−10°C ~ 50°C) / 30% ~ 80% RH
STORAGE TEMPERATURE / HUMIDITY	−4°F ~ 140°F(−20°C ~ 60°C) / 20% ~ 90% RH
POWER	DC12V [AC24V / DC12V DualPower (option)]

SIGNAL TRANSMISSION	The distant difference is occurred according to cable option and other circumstances. (coaxial cable 300M)