# Anti-IR Reflection | 4MP HD-TVI STORM® IR IP68 Vandal-Resistant Dome Camera with Motorized Vari-Focal Lens, L-Size, True WDR, DC 12V/AC 24V





1/2.9 inch ONY CMOS/ HD-TVI (1440P 30fps) • 0 Lux at IR On (IR LED 04 pcs) • Upgraded Waterproof Housing (IP 68 rating) • DOL WDR (WIDE DYNAMIC RANGE) • DNR (DIGITAL NOISE REDUCTION) • Day & Night (ICR Option) • Motorized 2.8~12mm Vari-focal Lens • AC24V / 12VDC Dual Power

## Mount Accessories

| | |
|---|---|
| Wall Mount Bracket | **DO WB221** |
| Ceiling Mount Bracket | **DO CB221** |

## SPECIFICATIONS

| | |
|---|---|
| Resolution | 1440P |
| Sensor | 1/2.9 inch 6Mega pixel SONY CMOS |
| Total Pixels | 3096(H) × 2218(V) = 6,866,928(pixel) |
| Effective Pixels | 3096(H) × 2202(V) = 6,817,392(pixel) |
| Electronic shutter speed | Auto / Manual ( 1/30(1/25)sec ~ 1/30000 sec) / FLICKER |

| | |
|---|---|
| SENSE UP | X2 / × 4 / × 8 / × 16 / × 32 |
| Video Output | TVI / CVBS: 1.0Vp-p (75ohm) |
| Min.Illumination | 0 Lux at IR On |
| White Balance | AUTO / AUTO EXT / PRESET / MANUAL |
| WDR / BLC / HLC | Off / WDR(Low / Middle / High) / BLC / HLC |
| Operating Temp./Hum | 14°F ~ 122°F(−10°C ~ 50°C) / Max 90%RH |
| Storage Temp./Hum | −4°F ~ 140°F(−20°C ~ 60°C) / Max 90%RH |
| DNR | OFF / LOW / MIDDLE / HIGH |
| ACE | OFF / LOW / MIDDLE / HIGH |
| Day & Night | Auto / Day / Night / Ext |
| PRIVACY | OFF / ON |
| MOTION | OFF / ON |
| DEFOG | OFF / ON |
| Smart IR | OFF / ON |
| Sharpness / Brightness | ADJUSTABLE (Sharpness : 0 ~ 10 STEP / Smart IR, Brightness : 0 ~ 20 STEP ) |
| Power | DC 12V / AC 24V |