EX-SDI 4MP Brick Camera with Dual Power, Lens not included

1/2.9 inch SONY CMOS (IMX-326) • High Definition Serial Digital Interface / 1 Lux at F1.2 / 0.1 Lux (B/W) • WDR (Wide Dynamic Range) • DNR (Digital Noise Reduction) • Day & Night • Lens not included

SPECIFICATIONS

Resolution	1440P, 1080P, 720P
Sensor	1/2.9 inch SONY CMOS (IMX-326)
Total Pixels	3096(H) × 2218(V) = 6.87M
Scanning System	PROGRESSIVE
S/N (Y signal)	More than 52 dB (AGC Off)
Video Output	SMPTE274M (EX-SDI, HD-SDI)
Min.Illumination	1 Lux at F1.2 / 0.1 Lux (B/W)
White Balance	AUTO / AUTO EXT / PRESET / MANUAL

Electronic shutter speed	AUTO / MANUAL (1/30sec ~ 1/30,000sec) / FLICKER
Brightness	ADJUSTABLE (0 ~ 20 STEP)
DNR	OFF / LOW / MIDDLE / HIGH
BACKLIGHT	OFF / WDR / BLC / HLC
Day & Night	AUTO (Day <--> Night TIME Change) , COLOR , B/W, EXTERN
PRIVACY / MOTION	OFF / ON
Language	ENG, CHN, CHN(S), JPN, KOR
Sharpness	ADJUSTABLE (0 ~ 10 STEP)
COMM.	RS-485(PELCO-D)
Temperature/Humidity	Operating (14°F ~ 122°F(−10°C ~ 50°C) / 30% ~ 80% RH) / Storage (−4°F ~ 140°F(−20°C ~ 60°C)/ 20% ~ 90% RH)
Power	AC24V / DC12V Dual Power
signal Transmission	The distant difference is occurred according to cable option and other circumstances. (based on 5C-HFBT : HD-SDI 100M / EX-SDI 500M)